



DF 480 763

fully integrated
Euro tub, appliance height 32 5/16"

DF 481 763

fully integrated
Tall tub, appliance height 34 1/8"

Included accessories

- 1 baking tray spray head
- 1 holder for Gastronorm inserts
- 1 holder for long-stemmed wine glasses

Installation accessories

DA 020 010

Stainless steel side trims for DF 480

DA 020 110

Stainless steel side trims for DF 481

DA 021 000

Folding hinge extends toe kick for fully-integrated look.

GZ 010 011

Aqua stop extension (78" long)
for all dishwashers.

Optional accessories

DA 042 030

Silvercare cartridge for all dishwashers

DA 043 000

Additional holder for long-stemmed glasses.
Offers safe positioning for up to four long-stemmed wine glasses during the dishwashing process and ensures an optimal cleaning result. For positioning in the lower basket.

DA 231 010

Stainless steel-backed full glass door panel with handle for DF 480 Euro tub dishwasher.

Height-adjustable by 2".

DA 231 110

Stainless steel-backed full glass door panel with handle for DF 481 Tall tub dishwasher.

Height-adjustable by 2".



400 series dishwasher

DF 480/DF 481

- Optimal protection for sensitive glassware by low temperature drying with zeolite and intelligent water softening
- 8 programs with aqua sensor and 5 options, such as Power and Intensive:
 - Clean and dry dishes in one hour.
 - Intensive cleaning in the lower basket while protecting glassware in the upper basket.
- Flexible rack system with smooth running rails on all levels and cushioned closing of the upper and lower racks
- TFT display for intuitive operation of all functions
- Remaining time projection onto the kitchen floor
- Back-light illumination for a perfectly bright interior
- Push-to-open function for a perfect integration into handleless cabinet fronts
- Very quiet: 42 dBA
- Aqua stop
- ENERGY STAR® certified

Operation

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water.
Touch key operation.
Information key with use indications.
Delayed start timer up to 24 hours.
Visual and acoustic end of program indicator.
Remaining time projection onto the kitchen floor.

Technical Features

Perfectly illuminated interior.
Glass protection with zeolite.
Aqua sensor.
Load sensor.
Automatic detergent function.
Regeneration electronics.
Heat exchanger.
Flow-through water heater.
Triple filter system.
Soft lock.
Aqua stop.

Home network integration for digital services (Home Connect) wireless via WiFi.
The use of Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Programs

8 programs:
Auto 150°F – 160°F.
Auto 127°F – 140°F.
Auto 113°F – 122°F.
Standard Eco 113°F – 136°F.
One Hour Wash 122°F (1 h.).
Quick Wash 113°F (30 min.).
Glass Care 122°F.
Pre-rinse.

5 cycle options:
Intensive.
Power.
Half Load.
Hygiene.
Zeo Dry (Extra Dry with Zeolite).

Features

Flexible rack system with smooth running rails on all levels and cushioned closing of the upper and lower racks.
3rd rack for cutlery.

Upper rack:

Over extension.
Rackmatic with 3 levels, adjustable in height up to 2".
6 folding tines.
4 folding racks.
2 glass support bars.

Lower rack:

8 folding tines.
2 folding racks.
Dividable glass support.
Cutlery basket.
Holder for long-stemmed glasses.

Maximum dish sizes for DF 480 (upper/lower rack)
8"/10", 7"/11" or 6"/12" respectively.

Maximum dish sizes for DF 481 (upper/lower rack)
9"/11", 8"/12" or 7"/13" respectively

12 place setting capacity.
Maximum glass loading capacity:
23 wine glasses.

Consumption data

Total annual energy consumption
269 kWh.
Water usage: 3.5 gallons.
Noise level: 42 dBA.

Planning notes


Height-adjustable feet.
Rear toe-kick protrusion 3 15/16" (see drawing).
To display the remaining time projection, a minimum toe-kick protrusion is required (1 5/16" + thickness of the cabinet front).
The maximum toe tick height must be reduced by 1 1/16" to provide an optimal display of the remaining time projection.
Rear feet adjustable at front.
Door weight up to 18 lbs. for DF 480 and 22 lbs. for DF 481.
Door panel dimension dependent on toe-kick height of kitchen cabinets.
Installation and usage also with cabinet handle possible. The push-to-open function remains active.
Water connection with 3/4" screw gland.
Connection to hot or cold water possible.

Please read further planning notes on pages 276–277.


Rating

Total rating: 1.4 kW.
Total Amps: 12 A.
120 V / 60 Hz
Connecting cable 47 1/4" with three-prong plug.


Euro Tub dishwasher DF 480



Tall Tub dishwasher DF 481



Connection dimensions for 24" wide dishwasher



[] values with extension kit