en Before using for the first time, read the instruction manual and the safety information it contains. **Programmes** Setting up Home Connect Overview of water hardness settings Setting the water softening sys-Dishwasher tem You can find an overview of the Medium 1.5 - 1.8 H:02 The programme data has been meas-Tip: Connect your appliance to a mobile device. You can conured in the laboratory according to water hardness values that can 1. Press (¹). veniently change all settings using the Home Connect app. Medium 1.9-2.1 H:03 European standard EN 60436. be selected here. 2.2 - 2.9 2. To open the basic settings, press Medium H·04 1. Install the Home Connect app on your mo-GET IT ON A table of country-specific units The consumption figures depend on 3 sec. for 3 seconds. 3.0 - 3.7 H.02 Google Play Hard bile device and follow the instructions. can be found in the instruction the programme and additional func-✓ The display shows H:xx. Hard 3.8 - 5.4 H:06 tion selected. manual. ✓ The display shows set. H:07 Hard 5.5 - 8.9 App Store The runtime will change if the rinse 3. Press Start repeatedly until the right Hardness mmol/l Setting aid system is switched off or rinse aid water hardness has been set. 2. Scan the QR code with the Home Connect value range needs to be added. 4. To save the settings, press 3 sec. app. Soft H:00 0 - 1.1 for 3 seconds. guide Programme 1) Duration [h:min] Soft 1.2 - 1.4 H:01 2) Energy [kWh] 3) Water [I] 1) 2:20 - 2:30 Ċ, 2) 1.000 - 1.100 Intensive 70° 3) 10.5 - 13.0 Quick reference 1) 1:38 - 1:50 AUTO 2) 0.600 - 0.700 Ì Adding special salt Ξ Auto 35-45°C 3) 9.8 - 13.5 1) 1:38 - 2:40 To avoid damage to the appliance, only add special 3. Add the special salt to the AUTO 2) 0.600 - 1.100 salt to the dispenser for special salt just before the dispenser. The water in the Auto 45-65° 3) 7.0 - 15.0 programme starts. dispenser is displaced and 1) 3:45 1. Unscrew the lid of the dispenser for special salt forced out. Never add de-Jæ, 2) 0.512 and remove. tergent. Eco 50° 3) 8.5 2. On initial start-up: Fill the dispenser right up with 1) 0:29 ,<u>78</u>, water. 4. Place the lid back on the dispenser and turn to 2)0.650close. Quick Wash 45°C 3) 10.0 1) 2:10 m 2) 1.220 * Adding rinse aid *Machine Care 3) 15.0 1) 0:15 - 0:15 1. Press the catch on the lid L 2. Add rinse aid up to the 2) 0.050 - 0.050 of the dispenser for rinse max mark. Personalisation function 3) 4.0 - 4.0 aid 1 and lift 2.

To cancel the programme, press Reset 4 sec. for approx. 4 seconds.
 The programme is cancelled and ends after approx. 1 minute.

CLICK

How to use your appliance

1. Load the tableware.

DF264101

(021102)

9001780546

Only clean tableware that is suitable for dishwashers. Remove large remnants of food from the tableware. Check that the spray arms can rotate freely.

///\

- 2. Add detergent.
- 3. Switch on the appliance ().

Adding detergent

1. Add the detergent to the

dry detergent dispenser.

4. Select the programme.

50 m

- 5. Start the programme Start.
- 6. Remove the tableware at the end of the programme.

3. Close the lid of the dispenser for rinse aid.

The lid clicks into position.

2. Close the lid of the deter-

gent dispenser.The lid clicks into position.

Cleaning filters

- 1. After each wash check the filters for residue.
- 2 Turn the coarse filter anticlockwise ① and remove the filter system ②.




3. Pull down the micro filter to remove.





- 5. Clean the filter elements under running water.
- **6.** Re-assemble the filter system.
- Insert the filter system into the appliance and turn the coarse filter clockwise. Make sure that the arrow markings match up.



4. Insert the lower spray arm.The spray arm clicks into position.

2


- 1. Unscrew the upper spray arms ① and pull down to remove ②.
- 2. Pull up the lower spray arm to remove.

3. Check the outlet nozzles on the spray arms for blockages un-

der running water and remove any foreign bodies.

5. Insert the upper spray arms and screw firmly in place.





- **1.** Disconnect the appliance from the power supply.
- **2.** Remove the filter system.
- **3.** Scoop out any water.
- **4.** Prise off the pump cover using a spoon and grip it by the crosspiece.



- **5.** Lift the pump cover inwards at an angle and remove.
- **6.** Remove any remnants of food and foreign bodies in the area of the impeller.
- 7. Insert the pump cover ① and press down ②.
- The pump cover clicks into position.



8. Install the filter system.

Troubleshooting

Cause and troubleshooting	Fault	Cause and troubleshooting	Fault	Cause and troubleshooting
Supply hose is kinked. • Install the supply hose without kinks.	E:92-40 will light up al- ternately.	Filters are soiled or blocked. • Clean the filters.	Removable streaks are present on glasses, glass- ware with a metallic ap- pearance and cutlery.	Amount of rinse aid to be dispensed is set too high. Set the rinse aid system to a lower setting.
 water supply lights up. Water tap is turned off. Turn on the water tap. Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 l/min when the water supply is open. The filters in the water connection of the supply or AquaStop hose are blocked. Switch off the appliance. Pull out the mains plug. Turn off the water tap. Unscrew the water connection. Remove the filter from the supply for the supply hose Clean the filter. Re-insert the filter in the supply hose. Screw the water connection back on. Check the water connection for leaks. Restore the power supply. 	E:61-02 will light up al- ternately.	Wastewater pump is blocked. • Clean the wastewater pump.		No rinse aid has been added. Add rinse aid.
		Cover of the wastewater pump is loose Secure the cover of the Wastewater pump so it clicks into position. 	Rust spots on cutlery.	Cutlery is not sufficiently rust-resistant. Knife blades are often more severely affected. • Use rust-resistant tableware.
	Remnants of food on tableware.	 Tableware is placed too close together or basket is overfilled. 1. Arrange tableware with sufficient space in between. The spray jets must reach the surfaces of the tableware. 2. Avoid points of contact. 		Cutlery may also rust if washed together with rusting items. Do not wash rusting items.
			 present in the detergent dispenser or the tablet collecting tray. 	 Spray arms were blocked by tableware so detergent was not rinsed out. Check that the spray arms are not blocked and can rotate freely. Electronics have detected a fault. Press the main switch button for approx. 4 seconds. The appliance is reset and restarted.
		 Spray arm rotation is blocked. Arrange tableware so that it does not obstruct spray arm ro- totion. 		
		Spray arm nozzles are blocked. Clean the Spray arms.		
		Filters are soiled. ► Clean the filters.		
		Filters are inserted incorrectly and/or not engaged. 1. Insert the filters properly. 2. Engage the filters.		
		 Washing programme selected too weak. Select a more intensive washing programme. Adjust the sensitivity of the sensors. 		
	 Supply hose is kinked. Install the supply hose without kinks. Water tap is turned off. Turn on the water tap. Water tap is jammed or furred up. Turn on the water tap. The flow rate must be at least 10 l/min when the water supply is open. The filters in the water connection of the supply or AquaStop hose are blocked. Switch off the appliance. Pull out the mains plug. Turn off the water connection. Remove the filter from the supply hose Clean the filter. Re-insert the filter in the supply hose. Screw the water connection back on. Check the water connection for leaks. 	Supply hose is kinked. E:92-40 will light up alternately. Yater tap is turned off. E:61-02 will light up alternately. Yater tap is jammed or furred up. E:61-02 will light up alternately. Yater tap is jammed or furred up. E:61-02 will light up alternately. Yater tap is jammed or furred up. E:61-02 will light up alternately. Yater tap is jammed or furred up. E:61-02 will light up alternately. Yater tap is jammed or furred up. E:61-02 will light up alternately. Yater tap is jammed or furred up. Remnants of food on tableware. Yater tap is open. Remnants of food on tableware. The filters in the water connection of the supply or AquaStop hose are blocked. Remnants of food on tableware. You see are blocked. You see are blocked. Remnants of food on tableware. You see are blocked. You see are tap. Remnants of food on tableware. You see are blocked. You see are connection. See are the filter from the supply hose. Subscience are the filter. Reinsert the filter in the supply hose. Screw the water connection back on. Scheck the water connection for leaks. Screw the water connection for leaks. Screw the water connection for leaks.	 Supply hose is kinked. Install the supply hose without kinks. E-92-40 will light up alternately. E-92-40 will light up alternately. Clean the filters. Clean the filters. Clean the differs. Clean the vater pump is blocked. Clean the water pump is blocked. Clean the water pump is loose Secure the cover of the wastewater pump is of the tableware. Pull out the mains plug. Turn of the water connection. Remove the filter from the supply hose. Screw the water connection back on. Clean the filters. Clean the filters. Filters are solied. Clean the filters. Filters are inserted incorrect	Supply hose is kinked. • Install the supply hose without kinks. Filters are soiled or blocked. • Clean the filters. Removable streaks are present on glasses, glassware with a metallic appearance and cutlery. Water tap is furned off. • Clean the water pump is blocked. • Clean the water pump is blocked. • Clean the water pump is loose • Clean the water pump is loose • Secure the cover of the Wastewater pump is obse • Secure the cover of the Wastewater pump is obse Rust spots on cutlery. The filters in the water connection of the supply or AquaStop hose are blocked. • Avoid points of contact. String of the appliance. • Avoid points of contact. Spray arm tableware is blocked. • Clean the filters. Supply hose • Clean the filter. • Secure the filter filters are soiled. • Clean the filters. • Clean the filters. Bernoarts of food mains plug. • Aring tableware is blocked. • Aring tableware so that it does not obstruct spray arm the detergent dispenser or the table ware. • Avoid points of contact. • Clean the filters. Secure the filter in the supply hose. • Clean the filters. • Clean the filters. • Clean the filters. • Clean the filters. Berower the filter in the supply hose. • Crean the filter seresoiled. • Clean the filters. • Clean the filters. • Clean the filters. Berower the filter

