GAGGENAU



AR 400 743

Metal housing 541 CFM Air extraction

Internal blower can only be used with 400 series AI/AW 442 island/ wall hood

For installation in the duct cover

400 series internal blower

- Powerful blower to combine with 400 series AW/AI 442 wall and island hood
- Quiet blower with high-efficiency BLDC technology
- Compact and space-saving due to the installation in the duct cover of AI/AW 442 island/wall hood

Output

3 performance output levels and Intensive mode.

Sound power and sound pressure depending on built-in situation. Air extraction: 541 CFM

Power levels depend on the power levels of the AW/AI 442 wall/ island hood.

Features

3 electronically controlled power levels and 1 intensive mode. Blower technology with highly efficient, brushless DC motor (BLDC).

Including sound insulation to minimize the noise level.
Duct connection piece on air output side: 1x ø 6" round.

Planning notes

Blower can only be combined with blowerless 400 series AI/AW 442 island/wall hood. Connection to the respective appliances via network cable. Installation in the duct cover of AI/ AW 442 island/wall hood.

Rating

Total rating: 200 W. Total Amps: 2 A. 120 V / 60 Hz

Connecting and network cable are included.

9⁷/₁₆" (240) 3³/₄" (95) 1¹/₈" (232) (233)