

The ceiling ventilations 200 series

The 200 series offers two exceptional ceiling ventilation solutions. The straightforward installation of both - the integrated and attached model – reduces both the time and cost normally associated with ceiling ventilation.

The ceiling ventilation AC 250

The AC 250 offers air extraction or recirculation in a minimalist, discrete unit that is integrated into the architecture. Utilising the powerful, energy saving and quiet brushless DC motor (BLDC), it is capable of extracting air at an impressive rate of 780 m³/h and recirculates it at 570 m³/h.

Type reference AC 250

Dimensions

90 cm Finishes

Stainless steel





The ceiling ventilation AC 231

Attaching directly to the ceiling, the AC 231, see above, provides powerful air recirculation, 850 m³/h at its highest setting. The glass cover makes cleaning simple and incorporates an indirect light that produces a back-lit, glowing effect.

Ceiling ventilation without compromises

Both ceiling ventilation options are operated by remote control, giving the chef three power levels, plus an intensive mode. Each model alerts the user when the grease filter needs to be cleaned in the dishwasher.

The 200 series offers two elegant ceiling solutions utilising our renowned ventilation expertise.

For further information see the models & dimensions or www.gaggenau.com.

Type reference AC 231

Dimensions 120 cm

Finishes

Stainless steel and glass



