

Color Variants

BO421101

Full glass door in Gaggenau Anthracite Width 60 cm

BO421101 Oven 400 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Controls at the top

Handleless door / automatic door opening

Pyrolytic system

9 heating methods, with baking stone function

TFT touch display

Panel-free appliance with surface control module

Electronic temperature control from 50 °C to 300 °C

Net volume 76 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling

Automatic door opening. Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes. Information key with use indicators. Side-opening door opens up to $180\,^{\circ}$ angle.

Features

Baking stone socket. Actual temperature display. Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing. Child lock. Safety shut-off. Cooled housing with temperature

protection.

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 47 mm from the furniture cavity.

If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.

Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 KW. Plan a connection cable.

Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in Integrated Cleaning system

Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions

595 x 590 x 547

Dimensions of the packed product

(HxWxD) (mm) 780 x 760 x 680

Control Panel Material

Door Material

Glass

Net weight (kg)

54.557

Usable volume of cavity (I)

76

Cooking method

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat

First cavity material

Number of interior lights

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

Interior Lights - cavity 1

Pull-out system

Accessory

Clock function

Alarm, Off, On, timer

Included accessories

Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W) 3000

Convection Element Wattages cavity 1 (W)

2100

Microwave wattage cavity 1 (W)

Drawer wattage (W)

Consumption and connection features

Energy efficiency rating

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection Rating (W)

3700

Current (A)

Voltage (V)

220-240 Frequency (Hz)

50

Plug type

no plug

Connecting cable type

Universal Product Code

Color / Material Front

Anthracite

Alternative colors available BO421111

Energy input

Electric

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (in)

Required cutout/niche size for installation (in)

ХХ

Dimensions of the packed product (in) 30.70 x 26.77 x 29.92

Net weight (lbs)



BO421101 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm Controls at the top

2020-10-11 Page 2







