



Color Variants

BOP220111
Full glass door in Gaggenau Metallic
Width 60 cm

BOP220111
Oven 200 series
Full glass door in Gaggenau Metallic
Width 60 cm

Flush installation
 Pyrolytic system
 9 heating methods, with baking stone function
 TFT touch display
 Panel-free appliance with surface control module
 Electronic temperature control from 50 °C to 300 °C
 Net volume 76 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling

Rotary knob and TFT touch display operation.
 Clear text display.
 Option to save individual recipes.
 Information key with use indicators.
 Side-opening door opens up to 110° angle.

Features

Baking stone socket.
 Actual temperature display.
 Rapid heating.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
 60 W halogen light on the top.
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
 Gaggenau enamel.
 Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
 The door panel surface of the appliance extends 21 mm from the furniture cavity.
 The outer edge of the door handle extends 72 mm from the furniture cavity.
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the 110° door opening angle.
 For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
 To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
 The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Characteristics

Color / Material Front
 Stainless steel

Built-in / Free-standing
 Built-in

Integrated Cleaning system
 Pyrolytic

Required niche size for installation (HxWxD)
 590-590 x 560-560 x 550

Dimensions
 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)
 780 x 760 x 680

Control Panel Material
 Glass

Door Material
 Glass

Net weight (kg)
 54.904

Usable volume of cavity (l)
 76

Cooking method
 Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat

First cavity material
 1

Number of interior lights
 1

Approval certificates
 Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)
 1

Interior Lights - cavity 1
 1

Pull-out system
 Accessory

Clock function
 Alarm, Off, On, timer

Included accessories
 Bake Element Wattages cavity 1 (W)
 Broil Element Wattages cavity 1 (W)
 3000
 Convection Element Wattages cavity 1 (W)
 2100
 Microwave wattage cavity 1 (W)
 Drawer wattage (W)

Consumption and connection features
Energy efficiency rating
 A

Energy consumption per cycle conventional (2010/30/EC)
 1.25

Energy consumption gas oven per cycle conventional (2010/30/EC)
 0.83

Energy consumption per cycle forced air convection (2010/30/EC)
 0.83

Energy consumption gas oven per cycle forced air convection (2010/30/EC)
 95.4

Energy efficiency index (2010/30/EC)
 95.4

Connection Rating (W)
 3700

Current (A)
 16

Voltage (V)
 220-240

Frequency (Hz)
 50

Plug type
 fixed connection, no plug

Connecting cable type
 Universal Product Code
 825225914495

Color / Material Front
 Stainless steel

Alternative colors available
 BOP220101, BOP220131

Energy input
 Electric

Approval certificates
 Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (in)
 Required cutout/niche size for installation (in)

Total connected load 3.7 KW.
 Plan a connection cable.

GAGGENAU

