



#### Color Variants

CI422101

Frameless

Width 38.3 cm

CI422101

Flex induction cooktop 400 series

Frameless

Width 38.3 cm

For combination within the set CVL 410

Flex function for combining the rectangular cooking areas  
Free positioning of cookware inside combined cooking areas  
Frying sensor function for temperature control in pans  
Easy control of all functions with bicoloured display  
Solid stainless steel control knob  
Frameless for flush mounting

#### Cooking zones

2 flex induction cooking areas 19x24 cm (2200 W, with booster 3700 W), linked together 38x24 cm (3300 W, with booster 3700 W).

#### Handling

Control knobs with illuminated ring, cooking zone and output level markings.  
Electronic power control in 12 stage (1...12).  
User friendly control with bicoloured display (white / orange).

#### Features

Flex function for rectangular cooking areas.  
Frying sensor function.  
Booster function.  
Stopwatch.  
Short-term timer.  
Options menu.

#### Safety

Individual residual heat indicators.  
Safety shut-off.

#### Planning notes

For combination within the sets CVL 410 and CVL 420.  
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.  
Appliance weight: approx. 10.

#### Connection

Total connected load 3.7 KW.  
Connecting cable 1.5 m without plug.

#### Characteristics

Product name/family

Vario/Domino cooking zone cera

Built-in / Free-standing

Built-in

Energy input

Electric

Total number of positions that can be used at the same time

2

Required niche size for installation

(HxWxD)

56 x 360-389 x 492-527

Width of the appliance

383

Dimensions

56 x 383 x 521

Dimensions of the packed product

(HxWxD) (mm)

130 x 580 x 600

Net weight (kg)

10.198

Gross weight (kg)

11.2

Residual heat indicator

Location of control panel

External control

Basic surface material

Ceramic

Color of surface

Black

Color of frame

Approval certificates

AENOR, CE

Length electrical supply cord (cm)

150

Connection Rating (W)

3700

Gas connection rating (W)

Current (A)

Voltage (V)

220-240

Frequency (Hz)

60; 50

#### Consumption and connection features

2021-02-24

Page 1

