



#### Color Variants

**CM450101**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

#### Included accessories

1 x assembly screws.  
 1 x scoop.  
 1 x test strip.  
 1 x milk container (insulated).  
 1 x connection hose for milk frother.  
 1 x milk pipe.

#### CM450101

**Fully automatic espresso machine 400 series**

**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

**Controls at the top**

Handleless door / automatic door opening  
 Continuous flow heater means no waiting time and constant brewing temperature  
 Aroma brewing technology for a full aroma  
 Single portion cleaning  
 TFT touch display  
 Panel-free appliance with surface control module  
 One-touch operation  
 Personalisation function  
 7 light settings  
 Electronic fill level control for milk, water and coffee to ensure a perfect result

#### Type of beverage

Ristretto / 2 x Ristretto.  
 Espresso / 2 x Espresso.  
 Espresso Macchiato / 2 x Espresso Macchiato.  
 Coffee / 2 x Coffee.  
 Americano / 2 x Americano.  
 Caffè Latte / 2 x Caffè Latte.  
 Latte Macchiato / 2 x Latte Macchiato.  
 Cappuccino / 2 x Cappuccino.  
 Flat White / 2 x Flat White.  
 Milk froth / 2 x Milk froth.  
 Warm milk / 2 x Warm milk.  
 Hot water / 2 x Hot water.

#### Handling

Automatic door opening.  
 Rotary knob and TFT touch display operation.  
 Clear text display.  
 Personalisation function, option to save 8 individualised beverages.  
 4 beverage size settings, volume can be individually adjusted to match the size of the cup.  
 8 coffee strength levels from very mild to extra strong.  
 Coffee: 3 grades.  
 Hot water: 10 grades.  
 4 coffee-milk ratio levels.  
 Adjustable grinding level.  
 Height-adjustable coffee dispenser 7 cm to 15 cm.  
 Easy access to water tank, milk and coffee bean container behind the door.

#### Features

Maintenance-free grinding unit with ceramic discs.  
 Separate drawer for second ground coffee type.  
 Water pump with 19 bar pressure.  
 Double grinding and brewing cycles for extra intensity for single beverage order.  
 For double beverage order, two grinding and brewing cycles.  
 Beverage dispenser with integrated milk system.  
 Insulated stainless steel milk container for up to 0.5 litres.  
 Integrated lightning with LEDs.  
 Removable bean container with aroma protecting lid for 500 g allows for an effortless exchange of different types of coffee beans.  
 Automatic adjustment of ground coffee quantity.  
 Removable 2.4 litre water tank.  
 Electronic water filter exchange indicator.

#### Characteristics

**Built-in / Free-standing**

Built-in

**Frothing nozzle**

No

**Display**

No

**Water protection system**

no

**Portion sizes**

All cups

**Dimensions**

455 x 590 x 444

**Dimensions of the packed product (HxWxD)**

545 x 475 x 670

**Required niche size for installation (HxWxD)**

449 x 558 x 347

**Hot water spout**

No

**Adjustable programs**

**Standby function**

Yes

**Pump pressure**

19

**Simultaneous preparation of 2 cups**

Yes

**Included accessories**

1 x assembly screws, 1 x scoop, 1 x test strip, 1 x milk container (insulated), 1 x connection hose for milk frother, 1 x milk pipe

**Optional accessories**

**Electrical connection rating**

1600

**Fuse protection**

10

**Voltage**

220-240

**Frequency**

50/60

**Plug type**

Gardy plug w/ earthing

**Product group**

Built-in coffee machine

**Brand**

Gaggenau

**Product name/family**

**Product name / Commercial code**

CM450101

**Universal Product Code**

**Main colour of product**

Anthracite

**Typology**

Fully automatic

Australia Standards, CE, Eurasian, G-Mark, Morocco, Ukraine, VDE

**Length electrical supply cord**

170.0

**Length of electrical supply cord (in)**

**Recommended height for installation (in)**

449

**Recommended height for installation**

449

**Appliance Dimensions (h x w x d) (in)**

**Dimensions**

455 x 590 x 444

**Dimensions of the packed product**

**Dimensions of the pallet (in)**

**Dimensions of the packed product (HxWxD)**

545 x 475 x 670

48

**Net weight**

21.932

54

**Gross weight**

24.4

**Capacity water container**

2.4

**Consumption and connection features**

2021-11-09

Page 1

Electronic fill level control for drip tray and container for coffee residue.

#### Safety

Child lock.

#### Cleaning


Fully automatic rinse programme when machine is turned on/off.  
 Automatic steam cleaning of the milk system after every beverage.  
 Automatic cleaning and descaling programme.  
 Emptying programme to prepare the appliance for holiday or transportation.  
 Empty-grinding function to remove coffee residues from the system when switching bean types.  
 Removable brewing unit.  
 Dishwasher-safe coffee residue container and drip tray.  
 Dishwasher-safe beverage dispenser.

#### Planning notes


Ideal installation height 95 cm to 145 cm (top edge of niche bottom).  
 The door panel surface of the appliance extends 47 mm from the furniture cavity.  
 When installing in a corner a side clearance is required.  
 Door opening angle appr. 110° (delivery status) - mounting distance to the wall has to be at least 350 mm.  
 Door opening angle appr. 155° - mounting distance to the wall has to be at least 650 mm.  
 Door opening angle appr. 92° - mounting distance to the wall has to be at least 100 mm (spare part No. 00636455).  
 Installation directly above 14 cm high warming drawer in 59 cm standardised niche.  
 Special accessories (order as spare parts):  
 Part No. 17000705 Water filter  
 Part No. 00311819 Descaling tablets  
 Part No. 00311769 Cleaning tablets  
 Part No. 00636455 Door hinge restrictor (92° opening angle)  
 Part No. 11015223 Bean container with lid

#### Connection

Total connected load 1.6 KW.



Left corner installation



If using the 92° door hinge restrictor (spare part no. 00636455), the minimum distance from the wall is only 100 mm.