



CMP250100

### Built-In Fully Automatic Coffee Machine 200 series

60 x 45 cm, Anthracite

CMP250100

#### Flush installation

Continuous flow heater means no waiting time and constant brewing temperature  
Aroma brewing technology for a full aroma  
Single portion cleaning  
TFT touch display  
One-touch operation  
Personalisation function  
7 light settings

#### Type of beverage

Espresso / 2 x Espresso.  
Coffee / 2 x Coffee. White coffee. Latte macchiato. Cappuccino. Milk froth. Warm milk. Hot water.

#### Handling

Rotary knob and TFT touch display operation.  
Clear text display in 25 languages.  
Personalisation function, option to save 8 individualised beverages.  
3 beverage size settings; can be individually adjusted to match the size of the cup.  
5 coffee strength levels from mild to extra strong.  
3 coffee and hot water temperature levels.  
4 grinding level settings.  
Height-adjustable coffee dispenser up to 15 cm.  
Automatic slide-out function.

#### Features

Grinding unit with ceramic discs.  
Separate container for second ground coffee type.  
Water pump with 19 bar pressure.  
Double grinding and brewing cycles for extra intensity for single beverage order.  
For double beverage order, two grinding and brewing cycles.  
Beverage dispenser with integrated milk system.  
Insulated milk container for up to 0.55 litres.  
Integrated lighting with 3 LEDs.  
Bean container for 1 kg.  
Automatic adjustment of ground coffee quantity.  
Removable 2.5 litre water tank.  
Electronic fill level control for water and coffee beans.  
Electronic water filter exchange indicator.  
Electronic fill level control for drip tray and container for coffee residue.

#### Safety

Child lock.  
Safety shut-off.

#### Cleaning

Fully automatic rinse programme when machine is turned on/off.  
Automatic quick rinsing of milk system.  
Automatic cleaning and descaling programme.  
Removable brewing unit.  
Dishwasher-safe coffee residue container and drip tray.  
Dishwasher-safe beverage dispenser.

#### Planning notes

Ideal installation height 95 cm (top edge of niche bottom), max. 120 cm.

Necessary lateral gap between appliance front and furniture panel of min. 5 mm.

The door panel surface of the appliance extends 21 mm from the furniture cavity.

When installing in a corner a side clearance of 200 mm is required.

Installation directly above 14 cm high warming drawer in 59 cm standardised niche.

Special accessories (order as spare parts):  
Part No. 467873 Water-filter cartridge Part No. 310967 Descaling tablets Part No. 310575 Cleaning tablets

#### Connection

Total connected load 1.7 KW.  
Connection cable 1.5 m with plug.

