



**RF200202**  
**Fully integrated, under-counter**  
**Niche width 60 cm, Niche height 82 cm**



Combines with cooler RC 200 (Side-by-side)  
 Net volume 98 litres  
 Cushioned door closing system allowing a soft and controlled door closure

**Technical Features**

Cushioned door closing system from 20° door opening angle, integrated in door hinge.  
 Malfunction signal.  
 Fast freezing.  
 Temperature range adjustable.  
 4-star freezer compartment.  
 Freezing capacity 12 kg/24 h.  
 Storage time after a malfunction 23 h.  
 3 freezer drawers.

**Consumption data**

Energy consumption 184 kWh/year.  
 Noise level 38 dB (re 1 pW).

**Planning notes**

Flat hinge.  
 Door hinge right, reversible.  
 Door opening angle of 115°, fixable at 90°.  
 Max. door panel weight 14 kg.  
 Height-adjustable feet.  
 Plinth height for niche height of 820 mm: 100 - 170 mm.  
 Plinth height for niche height of 870 mm: 150 - 220 mm.  
 The enclosed ventilation grille must be used.  
 The mains socket needs to be planned outside the built-in niche.

**Connection**

Total connected load 0.090 KW.  
 Connecting cable 2.3 m with plug.

**Color Variants**

**RF200202**  
**Niche width 60 cm, Niche height 82 cm**

**Included accessories**

2 x cold accumulator.  
 1 x ice cube tray.

**Characteristics**

**Energy Efficiency Class (Regulation (EU) 2017/1369)**  
 F

**Average annual energy consumption in kilowatt hour per year (kWh/a) (EU) 2017/1369**  
 224

**Sum of volume of frozen compartments (EU 2017/1369)**  
 106

**Airborne acoustical noise emissions (EU 2017/1369)**  
 38

**Airborne acoustical noise emission class (EU 2017/1369)**  
 C

**Product category**  
 Upright freezer

**Built-in / Free-standing**  
 Built-in

**Color / Material body**

**Frost free system**  
 No

**Climate class**  
 SN-ST

**Door panel options**  
 Possible but accessory

**Width of the appliance**  
 598

**Depth of the product**  
 548

**Dimensions of the packed product (HxWxD) (mm)**  
 890 x 610 x 670

**Required niche size for installation (HxWxD)**

**Warning signal / malfunction**  
 visual and audible

**Defrost process**  
 manual

**Cover door installation system**  
 Fixed-mounted

**Number of drawers/baskets (Stck)**  
 3

**Number of freezing flaps (Stck)**  
 0

**Lockable door**  
 No

**Thermometer freeze section**  
 Analog

**Light**  
 No

**Length electrical supply cord (cm)**  
 230

**Door hinge**  
 Right reversible

**Net weight (kg)**  
 35.550

**Gross weight (kg)**  
 38.5

**Multi-Flow Air Tower**  
 No

**Number of compressors**  
 1

**Number of independent cooling systems**  
 1

**Economy setting**  
 No

**Fast freezing switch**  
 Yes

**Number of Door Bins - Freezer**

**Door bin adjustability - Freezer**  
 No

**Tilt-out door bins in freezer**  
 No

**Number of shelves - Freezer**

**Door bin adjustability - Freezer**  
 No

**Shelf Material - Freezer**

**Reversible Door Hinge**  
 Yes

**Connection Rating (W)**  
 90

**Fuse protection (A)**  
 10

**Frequency (Hz)**  
 50

**Approval certificates**  
 CE, G-Mark, VDE

**Energy consumption (kWh)**  
 Total annual energy consumption (kWh)

