

RF461304	Vario built-in freezer 400 series 212.5 x 60.3 cm, soft close flat hinge RF461304	efficiency classes from A+++ to D. Energy consumption 284 kWh/year. Noise level 42 dB (re 1 pW).
1 x ice cube scoop 1 x connection set 1 x Ice storage container large	Stainless steel interior with solid anthracite aluminium elements Warm white and glare-free LED light spots Opening assist for door with two options: 1. Push-to-open function for integration into handleless furniture front 2. Pull-to-open function to facilitate opening the door using a handle	Planning notes Flat hinge. Door hinge left, reversible. Door opening angle of 115°, fixable at 90°.
RA448220: Ice container, small, 90° door fixation		In case of door opening angle of 90°, the drawers have restricted access and the standard ice storage container cannot be removed. A small ice storage container (RA 448 220) is available to ensure access. This change must be done prior to fixing the door.
RA450012: Water filter Vario 400	The drawers in the RC and RF models are positioned at the same height. With side-by-side installation, the glass shelves and door racks can be aligned on the same level Material and aesthetics of interior as for RC model - Glass shelves - Solid anthracite aluminium door racks	Max. door panel weight 41 kg. Shut-off valve for water connection must be planned next to the appliance and always be accessible. If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.
RA421610: SS door 61cm / 24"	Flat stainless steel inner door, full-length Almost invisible rail system for shelves and door racks for flexible positioning	
RA423140: Side trims, long	Integrated ice maker with fixed inlet water connection	Connection Total connected load: 0.300 KW. Connecting cable 3.0 m, detachable.
RA425110: Vario SS handle 1131 mm	TFT touch display Net volume 328 litres	Water inlet. Supply hose 2.0 m with 3/4 " connection.
RA428610: SS door w/o handle 61cm / 24"	Handling TFT touch display operation. Clear text display.	Water pressure 2 to 8 bar.
RA460013: Heating side kit 230V	Technical Features Dynamic cold air distribution. Automatic defrosting with defrost water evaporation. Rest mode certified by Star-K.	
RA460020: Frontpanel connection long	When rest mode is active, the appliance can only be opened using a handle. Open-door and malfunction alarm. Home network integration for digital services (Home Connect) wireless via WiFi.	
RA464616: Ventilation grille 61cm /24" with filter	The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com .	
	Freezing No-frost technology with fast freezing at -30 °C. Temperature adjustable from -24 °C to -14 °C. 4-star freezer compartment. Freezing capacity 18 kg/24 h. Storage time after a malfunction 13 h. 4 safety glass shelves, white glass, 3 of which are individually height adjustable. 2 fully extendable drawers with transparent front. Flat door rail system with fully flexible positioning of door racks. 4 height-adjustable door racks.	
	Ice maker Integrated in the freezer compartment, with fixed water connection (inlet). Particle filter for water inlet, integrated in ventilation grille area. Can be switched off. Ice cube production: approx. 1.5 kg/24 h. Removable ice storage container with approx. 4 kg capacity.	
	Consumption data Energy efficiency class A++ at a range of energy	

