



VI260114

VV200014:

Connecting strip series 200 ss

Vario induction hob 200 series

60 cm

VI260114

- Can be combined with the cooktops of the Vario 200 series to a harmonic unity
- Generous control panel for comfortable and secure operation
- 2 induction cooking zones ø 18 cm (1800 W, with booster 2500 W).
- 1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).
- Control knobs with cooking zone and output level markings.

- Can be combined with the cooktops of the Vario 200 series to a harmonic unity

Generous control panel for comfortable and secure operation

Cooking zones

2 induction cooking zones ø 18 cm (1800 W, with booster 2500 W).

1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling

Control knobs with cooking zone and output level markings.

Electronic control in 9 output levels.

Features

Cooking zone marking.

Pot detection.

Booster function for all cooking zones (two cooking zones - left and right - can be operated simultaneously with booster function).

Safety

Residual heat indication.

Operation indicator.

Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.

Immersion depth 49 mm.

Cooktop clamping range: 20 - 40 mm.

Intermediate shelf is recommended.

Appliance must be fixed from underneath.

Connection

Total connected load 7.4 KW.

Connecting cable 1.50 m without plug.

