



AC200160
Canopy extractor 200 series
Stainless steel and glass
Width 52 cm
Air extraction / Air recirculation

Can be integrated invisibly in upper cabinet
 Energy-saving, low-noise fan
 Rim extraction with flat and easy-to-clean glass underside
 Dimmable, neutral white LED light for ideal illumination of the whole cooktop
 Air extraction or air recirculation system

Output

Performance and noise level, output level 3/Intensive:
 Air output according to EN 61591.
 Sound power level according to EN 60704-3.
 Sound pressure level according to EN 60704-2-13.
 Odour reduction for air recirculation in accordance with EN 61591.
 Air extraction:
 550 / 725 m³/h.
 67 / 72 dB (A) re 1 pW.
 53 / 58 dB (A) re 20 µPa.
 Air recirculation:
 550 / 690 m³/h.
 72 / 77 dB (A) re 1 pW.
 58 / 63 dB (A) re 20 µPa.
 Odour reduction air recirculation 92 %.

Features

3 electronically controlled power levels and 1 intensive mode.
 Remote control is available as a special accessory.
 Interval ventilation, 6 min.
 Run-on function, 6 min.
 Grease filter saturation indicator.
 Metal grease filter, dishwasher-safe.
 Glass filter cover.
 Neutral white LED light (4000 K), dimmable.
 Lamp output 2 x 1 W.
 Illuminance 244 lx.
 Fan technology with highly efficient, brushless DC motor (BLDC).

Consumption data

Energy consumption 46.8 kWh/year.
 Sound level min. 44 dB / max. 67 dB normal mode.

Planning notes

Patented air recirculation module with activated charcoal filter can be installed in the upper cabinet. The activated carbon filter can be changed from the front by simply pulling out the filter drawer.
 The door of the upper cabinet must be fully open in order to change the activated charcoal filter.
 Can be integrated invisibly in upper cabinet.
 Vario cooktops with intensive production of vapours like VR/VP should be placed in the middle beneath the hood (in this case air recirculation is not recommended).
 Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).
 Clearance above electric appliances min. 50 cm.
 When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Characteristics

Product name/family
Color chimney
Typology
 Traditional
Approval certificates
 CE, Eurasian, G-Mark, Ukraine
Length electrical supply cord (cm)
 100
Required niche size for installation (HxWxD)
 418mm x 496.0mm x 264mm
Height of the chimney (mm)
Height of product, without chimney (mm)
Minimum distance above an electric hob
 500
Minimum distance above a gas hob
 650
Net weight (kg)
 10.098
Type of control
 Electronic
Number of speed settings
Maximum output air extraction (m³/h)
 550
Boost position output recirculating (m³/h)
 690.0
Maximum output recirculating air (m³/h)
Boost position air extraction (m³/h)
 725
Number of lights
 2
Noise level (dB)
 67
Diameter of air outlet (mm)
 120 / 150
Grease filter material
 Washable aluminium
EAN code
 4242006257460

Consumption and connection features

Connection Rating (W)
 272
Current (A)
 3
Voltage (V)
 220-240
Frequency (Hz)
 50
Plug type
 Gardy plug w/ earthing
Installation typology
 Built-in
2020-01-30
Page 1

Total connected load 272 W.
 Connecting cable 1.0 m with plug.

Color Variants

AC200160
Stainless steel and glass
Width 52 cm

Optional accessories

AA200510
Remote control for canopy extractor AC200

AC200160
Canopy extractor 200 series
Stainless steel and glass
Width 52 cm
Air extraction / Air recirculation
2020-01-30
Page 2

