



Color Variants

AI240120
stainless steel with stainless steel
control panel
Width 120 cm

Installation Accessories

AD200326
Stainless steel chimney extension
Length: 1100 mm
AD220396
Ceiling collar for chimneys
Stainless steel
AD223346
Extension for mounting kit 500 mm

AI240120
Island hood 200 series
stainless steel with stainless steel
control panel
Width 120 cm
Air extraction / Air recirculation
Delivery with mounting kit and chimney

Timeless, elegant design
Highly efficient extraction of cooking
vapours
Energy-saving, low-noise fan
Patented filter technology with high
grease absorption
Rim extraction filter with flat and
easy-to-clean stainless steel
underside
Function for automatic, sensor-
controlled power adjustment
depending on the build-up of cooking
vapours
Dimmable, neutral white LED light
for ideal illumination of the whole
cooktop
Air extraction or air recirculation
system
Air recirculation module with
activated charcoal filter: quiet and
highly efficient air recirculation
solution with odour reduction
in air extraction mode and long
replacement intervals

Output

Performance and noise level, output
level 3/Intensive: Air output according
to EN 61591. Sound power level
according to EN 60704-3. Sound
pressure level according to EN
60704-2-13. Odour reduction for air
recirculation in accordance with EN
61591.
Air extraction: 640 / 890 m³/h. 62 / 69
dB (A) re 1 pW. 48 / 55 dB (A) re 20
µPa.
Air recirculation: 470 / 570 m³/h. 68 /
72 dB (A) re 1 pW. 54 / 58 dB (A) re 20
µPa.
Odour reduction air recirculation 95%.

Features

3 electronically controlled power levels
and 1 intensive mode.
Automatic function with sensor-
controlled run-on function.
Grease filter saturation indicator.
Patented rim extraction filter,
dishwasher-safe.
Neutral white LED light (3600 K),
continuously dimmable.
Lamp output 4 x 5 W.
Illuminance 730 lx.
Fan technology with highly efficient,
brushless DC motor (BLDC).
Airflow-optimised interior for efficient
air circulation.
The package includes an one-way flap.

Consumption data

Energy consumption 51.6 kWh/year.
Sound level min. 40 dB / max. 62 dB
normal mode.

Planning notes

The package includes the mounting
kit and the two-part chimney with
the dimensions from 674 mm to 854
mm. Individual planning solutions can
be implemented using the special
accessory chimney extension AD 200
326 in combination with extension for
mounting kit AD 223 346.
Clearance above gas appliances min.
65 cm (more than total load gas 12 kW
min. 70 cm).
Clearance above electric appliances
min. 55 cm.
The air recirculation module with
activated charcoal filter can be installed
on the inner chimney.

Characteristics

Product name/family
Color chimney
Typology
Chimney
Approval certificates
Australia Standards, CE, Eurasian, G-
Mark, Ukraine, VDE
Length electrical supply cord (cm)
130
Required niche size for installation
(HxWxD)
Height of the chimney (mm)
674-854
Height of product, without chimney
(mm)
70
Minimum distance above an electric
hob
550
Minimum distance above a gas hob
650
Net weight (kg)
41.417
Type of control
Electronic
Number of speed settings
Maximum output air extraction (m3/h)
640
Boost position output recirculating
(m3/h)
570.0
Maximum output recirculating air (m3/
h)
Boost position air extraction (m³/h)
890
Number of lights
4
Noise level (dB)
62
Diameter of air outlet (mm)
120 / 150
Grease filter material
Washable stainless steel
EAN code
4242006234652

Consumption and connection features

Connection Rating (W)
280
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
60; 50
Plug type
Gardy plug w/ earthing
Installation typology
Island
2020-01-19
Page 1

When installing a ventilation hood with
air extraction mode and a chimney-
vented fireplace, the power supply line
of the ventilation appliance needs a
suitable safety switch.

Connection

Total connected load 280 W.
Connecting cable 1.3 m with plug.