



#### Color Variants

**AW240120**  
stainless steel with stainless steel  
control panel  
Width 120 cm

#### Installation Accessories

**AD200322**  
Stainless steel chimney extension  
Length: 1000 mm  
**AD200392**  
Ceiling collar for chimneys  
Stainless steel

**AW240120**  
**Wall-mounted hood 200 series**  
stainless steel with stainless steel  
control panel  
**Width 120 cm**  
**Air extraction / Air recirculation**  
**Delivery with chimney**

Timeless, elegant design  
Highly efficient extraction of cooking  
vapours  
Energy-saving, low-noise fan  
Patented filter technology with high  
grease absorption  
Rim extraction filter with flat and  
easy-to-clean stainless steel  
underside  
Function for automatic, sensor-  
controlled power adjustment  
depending on the build-up of cooking  
vapours  
Dimmable, neutral white LED light  
for ideal illumination of the whole  
cooktop  
Air extraction or air recirculation  
system  
Air recirculation module with  
activated charcoal filter: quiet and  
highly efficient air recirculation  
solution with odour reduction as  
in air extraction mode and long  
replacement intervals

#### Output

Performance and noise level, output  
level 3/Intensive:  
Air output according to EN 61591.  
Sound power level according to EN  
60704-3.  
Sound pressure level according to EN  
60704-2-13.  
Odour reduction for air recirculation in  
accordance with EN 61591.  
Air extraction:  
600 / 800 m<sup>3</sup>/h.  
64 / 70 dB (A) re 1 pW.  
50 / 56 dB (A) re 20 µPa.  
Air recirculation:  
400 / 460 m<sup>3</sup>/h.  
65 / 68 dB (A) re 1 pW.  
51 / 54 dB (A) re 20 µPa.  
Odour reduction air recirculation 95%.

#### Features

3 electronically controlled power levels  
and 1 intensive mode.  
Automatic function with sensor-  
controlled run-on function.  
Grease filter saturation indicator.  
Patented rim extraction filter,  
dishwasher-safe.  
Neutral white LED light (3600 K),  
continuously dimmable.  
Lamp output 4 x 5 W.  
Illuminance 929 lx.  
Fan technology with highly efficient,  
brushless DC motor (BLDC).  
Airflow-optimised interior for efficient  
air circulation.  
Easy mounting system for simple  
installation and alignment.  
The package includes an one-way flap.

#### Consumption data

Energy consumption 45.5 kWh/year.  
Sound level min. 43 dB / max. 64 dB  
normal mode.

#### Planning notes

The package includes the two-part  
chimney with the dimensions from 582  
mm to 884 mm. Individual planning  
solutions can be implemented using  
the special accessory chimney  
extension AD 200 322 or by shortening  
the lower edge of the inner chimney.  
Clearance above gas appliances min.  
65 cm (more than total load gas 12 kW  
min. 70 cm).  
Clearance above electric appliances  
min. 55 cm.

#### Characteristics

**Product name/family**  
**Color chimney**  
**Typology**  
Chimney  
**Approval certificates**  
CE, Eurasian, G-Mark, Ukraine, VDE  
**Length electrical supply cord (cm)**  
130  
**Required niche size for installation  
(HxWxD)**  
**Height of the chimney (mm)**  
582-884  
**Height of product, without chimney  
(mm)**  
70  
**Minimum distance above an electric  
hob**  
550  
**Minimum distance above a gas hob**  
650  
**Net weight (kg)**  
25.800  
**Type of control**  
Electronic  
**Number of speed settings**  
**Maximum output air extraction (m<sup>3</sup>/h)**  
634  
**Boost position output recirculating  
(m<sup>3</sup>/h)**  
460.0  
**Maximum output recirculating air (m<sup>3</sup>/  
h)**  
**Boost position air extraction (m<sup>3</sup>/h)**  
800  
**Number of lights**  
4  
**Noise level (dB)**  
64  
**Diameter of air outlet (mm)**  
120 / 150  
**Grease filter material**  
Washable stainless steel  
**EAN code**  
4242006238735

#### Consumption and connection features

**Connection Rating (W)**  
280  
**Current (A)**  
10  
**Voltage (V)**  
220-240  
**Frequency (Hz)**  
50; 60  
**Plug type**  
Gardy plug w/ earthing  
**Installation typology**  
Wall-mounted

2020-02-27

Page 1

The air recirculation module with  
activated charcoal filter can be installed  
on the external chimney or inner  
chimney.

When installing a ventilation hood with  
air extraction mode and a chimney-  
vented fireplace, the power supply line  
of the ventilation appliance needs a  
suitable safety switch.

#### Connection

Total connected load 280 W.  
Connecting cable 1.3 m with plug.