



Color Variants

AW240190
stainless steel with stainless steel
control panel
Width 90 cm

Installation Accessories

AD200322
Stainless steel chimney extension
Length: 1000 mm
AD200392
Ceiling collar for chimneys
Stainless steel

AW240190
Wall-mounted hood 200 series
stainless steel with stainless steel
control panel
Width 90 cm
Air extraction / Air recirculation
Delivery with chimney

Timeless, elegant design
Highly efficient extraction of cooking
vapours
Energy-saving, low-noise fan
Patented filter technology with high
grease absorption
Rim extraction filter with flat and
easy-to-clean stainless steel
underside
Function for automatic, sensor-
controlled power adjustment
depending on the build-up of cooking
vapours
Dimmable, neutral white LED light
for ideal illumination of the whole
cooktop
Air extraction or air recirculation
system
Air recirculation module with
activated charcoal filter: quiet and
highly efficient air recirculation
solution with odour reduction as
in air extraction mode and long
replacement intervals

Output

Performance and noise level, output
level 3/Intensive:
Air output according to EN 61591.
Sound power level according to EN
60704-3.
Sound pressure level according to EN
60704-2-13.
Odour reduction for air recirculation in
accordance with EN 61591.
Air extraction:
610 / 810 m³/h.
66 / 72 dB (A) re 1 pW.
52 / 58 dB (A) re 20 µPa.
Air recirculation:
450 / 530 m³/h.
70 / 74 dB (A) re 1 pW.
56 / 60 dB (A) re 20 µPa.
Odour reduction air recirculation 95%.

Features

3 electronically controlled power levels
and 1 intensive mode.
Automatic function with sensor-
controlled run-on function.
Grease filter saturation indicator.
Patented rim extraction filter,
dishwasher-safe.
Neutral white LED light (3600 K),
continuously dimmable.
Lamp output 3 x 5 W.
Illuminance 731 lx.
Fan technology with highly efficient,
brushless DC motor (BLDC).
Airflow-optimised interior for efficient
air circulation.
Easy mounting system for simple
installation and alignment.
The package includes an one-way flap.

Consumption data

Energy consumption 38.8 kWh/year.
Sound level min. 44 dB / max. 66 dB
normal mode.

Planning notes

The package includes the two-part
chimney with the dimensions from 582
mm to 884 mm. Individual planning
solutions can be implemented using
the special accessory chimney
extension AD 200 322 or by shortening
the lower edge of the inner chimney.
Clearance above gas appliances min.
65 cm (more than total load gas 12 kW
min. 70 cm).
Clearance above electric appliances
min. 55 cm.

| Characteristics |
|---|
| Product name/family |
| Color chimney |
| Typology |
| Chimney |
| Approval certificates |
| Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE |
| Length electrical supply cord (cm) |
| 130 |
| Required niche size for installation (HxWxD) |
| Height of the chimney (mm) |
| 582-884 |
| Height of product, without chimney (mm) |
| 70 |
| Minimum distance above an electric hob |
| 550 |
| Minimum distance above a gas hob |
| 650 |
| Net weight (kg) |
| 22.063 |
| Type of control |
| Electronic |
| Number of speed settings |
| Maximum output air extraction (m3/h) |
| 610 |
| Boost position output recirculating (m3/h) |
| 530.0 |
| Maximum output recirculating air (m3/h) |
| Boost position air extraction (m³/h) |
| 810 |
| Number of lights |
| 3 |
| Noise level (dB) |
| 66 |
| Diameter of air outlet (mm) |
| 120 / 150 |
| Grease filter material |
| Washable stainless steel |
| EAN code |
| 4242006234621 |

| Consumption and connection features |
|-------------------------------------|
| Connection Rating (W) |
| 275 |
| Current (A) |
| 10 |
| Voltage (V) |
| 220-240 |
| Frequency (Hz) |
| 60; 50 |
| Plug type |
| Gardy plug w/ earthing |
| Installation typology |
| Wall-mounted |

2020-02-19
Page 1

The air recirculation module with
activated charcoal filter can be installed
on the external chimney or inner
chimney.
When installing a ventilation hood with
air extraction mode and a chimney-
vented fireplace, the power supply line
of the ventilation appliance needs a
suitable safety switch.

Connection

Total connected load 275 W.
Connecting cable 1.3 m with plug.