



BM454110

combi-microwave oven 400 series
60 x 45 cm, door hinge: right, Stainless steel
behind glass
BM454110

- Handleless door / automatic door opening
 - Combination of microwave, grill and oven
 - Sequential operation of up to 5 modes including programming of combined operation and rest time
 - Handleless door / automatic door opening
- Single operation and combination of microwave, grill and oven
 Sequential operation of up to 5 modes incl. programing of combined operation and rest time
 TFT touch display
 Panel-free appliance with surface control module
 Electronic temperature control
 Interior volume 36 litres

Programs

Microwave operation with 5 output levels: 1000, 600, 360, 180, 90 W.
 Oven operation with 4 heating methods:
 Hot air 40 °C and from 100 °C to 250 °C,
 Full surface grill + hot air from 100 °C to 250 °C,
 Full surface grill + circulated air from 100 °C to 250 °C,
 Full surface grill with 3 levels of intensity, maximum output 2000 W.
 Heating methods with microwave output levels 600, 360, 180 and 90 W freely combinable.
 15 automatic programs with weight indication, customisable:
 4 defrosting programs
 4 cooking programs
 7 combination programs

Handling

Automatic door opening.
 Rotary knob and TFT touch display operation.
 Information key with use indicators.
 Side-opening door opens up to 180° angle.

Features

Rapid heating.
 4 tray levels.
 Actual temperature display.
 60 W halogen light on the side.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).

Safety

Thermally insulated door with triple glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning

Hygienic stainless steel interior with glass ceramic base.
 Interior back wall with catalytic coating.


Planning notes

Door hinge not reversible.
 Plan the niche without back wall.
 The door panel surface of the appliance extends 47 mm from the furniture cavity.

Consider the overhang when planning to open drawers next to the appliance.
 The mains socket needs to be planned outside of the built-in niche.

Connection

Total connected load 3.1 KW.
 Connection cable 1.5 m without plug.



Socket
measurements in mm

Side view of BM 454/455 above BO

