



BO470112

BS020002:

Set of 2 pizza paddles

GN340230:

Gastronorm roaster GN 2/3

BA016105:

1 telescopic shelf rail, for 60cm oven

BA026105:

Grill tray, for oven BO47*

BA026115:

Baking tray, for 60cm oven

BA036105:

wire rack, for 60cm oven

BA046117:

Glass tray, for 60cm oven

BA056115:

Heating elem. 230 V, for 60cm oven

BA056133:

Baking stone for 60 cm oven

oven 400 series

60 x 60 cm, door hinge: right, Stainless steel
behind glass

BO470112

- Handleless door / automatic door opening
 - Pyrolytic cleaning programme heats up to 485 °C
 - 17 heating methods with core temperature probe, rotisserie spit and baking stone function
 - Automatic programmes
 - The 3-point core temperature sensor measures precisely the temperature and revises the cooking times as the dish is cooking.
 - Handleless door / automatic door opening / door opening via voice assistant possible
- Pyrolytic system
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
Automatic programs
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proving.
Defrosting.
Keeping warm.

Handling

Automatic door opening.
Rotary knob and TFT touch display operation.
Option to save individual recipes (incl. core temperature probe).
Personalisation of automatic programs.
Information key with use indicators.
Side-opening door opens up to 180° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.
Automatic programs.
Rotisserie spit.
Baking stone socket.
Actual temperature display.
Rapid heating.
60 W halogen light on the top.
2 x 10 W halogen light on the side.
Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).


Safety

Thermally insulated door with quadruple glazing.


Child lock.

Safety shut-off.


When installed next to each other




Cross section of the top/bottom door edge gaps



Air inlet cross section at the door edges



Measurements in mm



* 200 mm in conjunction with BA 016