



#### Color Variants

<b>BOP220101</b>
Full glass door in Gaggenau Anthracite
Width 60 cm
<b>BOP220111</b>
Full glass door in Gaggenau Metallic
Width 60 cm

#### Included accessories

1 x enamel baking tray.
suit. pyrolytic clean.
1 x glass pan.
1 x grill shelf.

#### Optional accessories

<b>BA016105</b>
Pull-out system for 60cm ovens
<b>BA056115</b>
Heating element for baking stone and
Gastronorm roaster.
<b>BA056133</b>
Baking stone.
<b>GN340230</b>
Gastronorm roaster in cast aluminium.

#### Product Variants

<b>BOP221101</b>
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Left-hinged

<b>BOP220101</b>
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged

Flush installation
Pyrolytic system
9 heating methods, with baking stone
function
TFT touch display
Panel-free appliance with surface
control module
Electronic temperature control from
50 °C to 300 °C
Net volume 76 litres

#### Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top heat.
Bottom heat.
Hot air + bottom heat.
Full surface grill + circulated air.
Full surface grill.
Baking stone function.

#### Handling

Rotary knob and TFT touch display
operation.
Option to save individual recipes.
Side-opening door opens up to 110°
angle.

#### Features

Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking
time end, timer, stopwatch, long-term
timer.
60 W halogen light on the top.
Enamelled side shelf supports with 4
tray levels, pyrolysis-safe.

#### Safety

Information key with use indicators.
Thermally insulated door with quintuple
glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature
protection.

#### Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.
The door panel surface of the
appliance extends 21 mm from the
furniture cavity.
The outer edge of the door handle
extends 72 mm from the furniture
cavity.
Necessary lateral gap between
appliance door and furniture panel of
min. 5 mm.
Consider the overhang, incl. the door
handle, when planning to open drawers
next to the appliance.
When planning a corner solution, pay
attention to the 110° door opening
angle.

#### Connection

Total connected load 3.7 kW.
For installation underneath cooktops:
Distance between the underside of the
cooktop and the top edge of the oven
cavity: min. 15 mm. The planning notes
for the cooktops (particularly regarding
ventilation, gas/electric connection)
must be taken into account.

Characteristics
Color / Material Front
Anthracite
Built-in / Free-standing
Built-in
Integrated Cleaning system
Pyrolytic
Required niche size for installation
(HxWxD)
590-590 x 560-560 x 550
Dimensions of the product (mm)
595 x 590 x 547
Dimensions of the packed product
(HxWxD) (mm)
780 x 760 x 680
Control Panel Material
without panel
Door Material
Glass
Net weight (kg)
55.283
Usable volume of cavity (l)
76
Cooking method
Baking stone function, Bottom heat,
Conventional heat, Full width grill, Hot
Air, Hot air and 1/1 bottom heating, Hot
Air-Eco, Hot air grilling, Top heat
First cavity material
Enamelled
Temperature control
electronic
Number of interior lights
1
Approval certificates
Australia Standards, CCC, CE, China,
China ROHS 20, Eurasian, Ukraine, VDE
Length electrical supply cord (cm)
EAN code
4242006242688

Consumption and connection features
Number of cavities (2010/30/EC)
1
Energy efficiency class (2010/30/EC)
A
Energy consumption per cycle
conventional (2010/30/EC)
1.25
Energy consumption gas oven per cycle
conventional (2010/30/EC)
Energy consumption per cycle forced
air convection (2010/30/EC)
0.83
Energy consumption gas oven per cycle
forced air convection (2010/30/EC)
Energy efficiency index (2010/30/EC)
95.4
Connection Rating (W)
3700
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug

2019-09-24

Page 1

