

Color Variants BOP251111 Full glass door in Gaggenau Metallic Width 60 cm BOP251101 Full glass door in Gaggenau Anthracite Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x glass pan. 1 x arill shelf. 1 x pluggable meat probe

Optional accessories BA016105 Pull-out system BA056115 Heating element for baking stone and Gastronorm roaster. BA056133 Baking stone GN340230 Gastronorm roaster in cast aluminium.

Product Variants BOP250111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm

BOP251111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm

Flush installation Pyrolytic system 13 heating methods, with core temperature probe and baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C Net volume 76 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

Handling

Rotary knob and TFT touch display operation. Option to save individual recipes (incl. core temperature probe). Information key with use indicators. Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off. Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer 60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing. Child lock Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account. To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Connection



GAGGENAU

Characteristics Color / Material Front Stainless steel Built-in / Free-standing Built-in Integrated Cleaning system Pyrolytic Required niche size for installation (HxWxD) 590-590 x 560-560 x 550 Dimensions of the product (mm) 595 x 590 x 547 Dimensions of the packed product (HxWxD) (mm) 780 x 760 x 680 Control Panel Material Door Material Glass Net weight (kg) 54.699

Usable volume of cavity (I) 76

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat First cavity material

Oven control electronic

Number of interior lights

Approval certificates Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE Length electrical supply cord (cm) EAN code

4242006242510

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1 25

Energy consumption gas oven per cycle conventional (2010/30/EC) Energy consumption per cycle forced air convection (2010/30/EC)

0.83 Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC) 95.4

Connection Rating (W) 3700

Current (A) 16

Voltage (V) 220-240

Frequency (Hz) 50

Plug type fixed connection, no plug

2020-07-18 Page 1

Total connected load 3.7 KW. Plan a connection cable.

BOP251111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm 2020-07-18 Page 2



