



CX482100
Full surface induction cooktop 400 series
Frameless
Width 80 cm

One single large cooking surface
Free positioning of cookware
All sizes and formats of cookware can be used
TFT touch display for an intuitive control of all functions
Cooking sensor function for temperature control in pots
Professional cooking function
Max. power output for big cookware of up to 5.5 KW
Frameless for flush mounting

Cooking zones

Up to 5 items of cookware can be placed simultaneously on the cooktop.
One unique cooking surface of 2750 cm².

Handling

Easy to use colour graphic TFT touch display with use indications.
Electronic power control in 17 output levels.

Features

Cooking sensor function.
Professional cooking function.
Dynamic cooking function.
Teppan Yaki function.
Booster function for pots.
Booster function for pans.
Keep warm function.
Individual pot detection.
Cooking timer for each cooking position.
Stopwatch.
Short-term timer.
Information key with use indicators.
Power management.

Safety

Main switch.
Child lock.
Safety shut-off.
Pause function.

Planning notes

Appliance must be fixed from underneath.
The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads.
Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.
The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.
Joint width may vary due to dimensional tolerances of the glass ceramic cooktop and the worktop cut-out.
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.
The wok pan WP 400 001 cannot be used with this appliance.
Appliance weight: approx. 27.

Connection

Total connected load 7.4 KW.
Connecting cable 1.5 m without plug.
Power consumption standby/display off 0.5 W.

Characteristics

Product name/family
Cooking zone ceramic

Construction type
Built-in

Energy input
Electric

Total number of positions that can be used at the same time
5

Type of control setting devices
Required niche size for installation (HxWxD)

Width of the appliance
793

Dimensions (HxWxD)
76 x 793 x 513

Dimensions of the packed product (HxWxD)
152 x 951 x 636

Net weight
27.200

Gross weight
29.1

Residual heat indicator
separate

Location of control panel
Hob front

Type of external control possibility
Basic surface material

Color of surface
anthracite

Color of frame

Approval certificates
AENOR, CE

Length electrical supply cord
150

EAN code
4242006268794

Electrical connection rating
7400

Gas connection rating

Fuse protection

Voltage
220-240

Frequency
60; 50

Consumption and connection features

2021-10-20
Page 1

Color Variants

CX482100
Frameless
Width 80 cm

Included accessories

1 x wireless temperature sensor for cooktop.

