



Color Variants

VL040115
Stainless steel control panel
Width 8.5 cm

Installation Accessories

AD724041
Round duct connection additional adapter for VL414/VL040/VL041 on the side
Metal zinc coated

AD724042
Connection piece for round pipe DN 150

AD854046
Flat duct system with guidance fins
Connecting piece VL 414 and VL040/VL041 for DN 150 flat

LS041001
Stainless steel

VV200014
Stainless steel connection strip for combination with further Vario cooktops

VL040115
Vario downdraft ventilation 200 series
Stainless steel control panel
Width 8.5 cm
Expansion element
Air extraction/air recirculation with remote fan unit AR 403/413 121

Ventilation element integrated in the worktop
Highly efficient ventilation system at the cooktop
Minimal planning and easy installation for air recirculation

Output

Power levels depend on the remote fan unit, see table on page XX.

Features

Ventilation grille, washable.
Metal grease filter with grease drip tray, dishwasher-safe.
No duct connecting piece included.

Planning notes

Only in combination with VL 041 115.
Air extraction in combination with remote fan unit AR 403 121 or air recirculation mode with AR 413 121.
Maximum cooktop width between 2 VL: 60 cm (exception: VI/VE 270).
If installed next to gas appliances, the ventilation moulding LS 041 001 is recommended to ensure maximum performance of the cooktop. If installed next to gas appliances, flat ducts must not be used for the piping up to the fan unit.
When having installed the ventilation moulding LS 041 001 the wok pan WP 400 001 can not be used.
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Connecting cable 2.0 m with plug.

Characteristics

Product name/family
Color chimney
Typology
Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
200
Required niche size for installation (HxWxD)
320mm x 78.0mm x 490mm
Height of the chimney (mm)
Height of product, without chimney (mm)
Minimum distance above an electric hob
Minimum distance above a gas hob
Net weight (kg)
1.335
Type of control
Number of speed settings
Maximum output air extraction (m³/h)
Boost position output recirculating (m³/h)
Maximum output recirculating air (m³/h)
Boost position air extraction (m³/h)
Number of lights
Noise level (dB)
Diameter of air outlet (mm)
150
Grease filter material
Washable aluminium
EAN code
4242006239794

Consumption and connection features

Connection Rating (W)
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
Installation typology
Built-in
2020-02-20
Page 1