



Color Variants

VL041115
Stainless steel control panel
Width 8.5 cm

Installation Accessories

AD724041
Round duct connection additional
adapter for VL414/VL040/VL041 on the
side
Metal zinc coated
AD724042
Connection piece for round pipe DN
150
AD854046
Flat duct system with guidance fins
Connecting piece VL 414 and VL040/
VL041 for DN 150 flat
LS041001
Stainless steel
VV200014
Stainless steel connection strip
for combination with further Vario
cooktops

VL041115
Vario downdraft ventilation 200 series
Stainless steel control panel
Width 8.5 cm
Control unit
Air extraction/air recirculation with
remote fan unit AR 403/413 121

Ventilation element integrated in the
worktop
Highly efficient ventilation system at
the cooktop
Minimal planning and easy
installation for air recirculation

Features

Output control, knob operation.
4 output levels.
Ventilation grille, washable.
Metal grease filter with grease drip tray,
dishwasher-safe.
No duct connecting piece included.

Consumption data

Consumption data is referred to a
configuration with the remote fan unit
AR 403 121.
Energy consumption 70 kWh/year.
Sound level min. 52 dB / max. 67 dB
normal mode.

Planning notes

No additional switch necessary.
Air extraction in combination with
remote fan unit AR 403 121 or air
recirculation mode with AR 413 121.
Maximum cooktop width between 2 VL:
60 cm (exception: VI/VE 270).
If installed next to gas appliances,
the ventilation moulding LS 041 001
is recommended to ensure maximum
performance of the cooktop. If installed
next to gas appliances, flat ducts must
not be used for the piping up to the fan
unit.
When having installed the ventilation
moulding LS 041 001 the wok pan WP
400 001 can not be used.
When installing a ventilation hood with
air extraction mode and a chimney-
vented fireplace, the hood's power
supply line needs a suitable safety
switch.
Please read additional planning notes
on page xx.

Connection

Connecting cable 1.5 m with plug.

Characteristics

Product name/family
Color chimney
Typology
Approval certificates
Australia Standards, CE, Eurasian, G-
Mark, Ukraine, VDE
Length electrical supply cord (cm)
150
Required niche size for installation
(HxWxD)
320mm x 78.0mm x 490mm
Height of the chimney (mm)
Height of product, without chimney
(mm)
Minimum distance above an electric
hob
Minimum distance above a gas hob
Net weight (kg)
2.535
Type of control
mechanical
Number of speed settings
4
Maximum output air extraction (m3/h)
440
Boost position output recirculating
(m3/h)
Maximum output recirculating air (m3/
h)
Boost position air extraction (m³/h)
Number of lights
Noise level (dB)
67
Diameter of air outlet (mm)
150
Grease filter material
Washable aluminium
EAN code
4242006239770
Consumption and connection features
Connection Rating (W)
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
Installation typology
Built-in
2020-02-20
Page 1