



**AH900761**  
24" visor hood for exhaust/recirculating  
air operation

Stainless steel-colored handle strip  
Technology concealed - design  
revealed  
Top performance with low noise -  
optimum benefit with minimal sound  
Eight-key operation - direct access to  
all functions  
Metal grease filter, dishwasher safe  
7-inch pull-out steam visor  
Front operation; handle strip not  
replaceable  
Bright cooking area illumination by  
compact fluorescent lamp: 36 Watts  
Three electronically controlled  
speeds plus intensive mode  
Delayed shut-off function  
Special function: interval ventilation  
Grease filter saturation indicator.  
ø 6" exhaust air pipe  
max. unobstructed airflow : 660 m<sup>3</sup> /  
h  
Exhaust mode DIN EN 61591 : 600  
m<sup>3</sup> / h  
Recirculation mode DIN EN 61591:  
370 m<sup>3</sup> / h  
Sound pressure level with ø 6"  
ducting:  
Exhaust air: 54 dB  
Air circulation: 64 dB  
Total rating : 250 W

**Color Variants**

AH900761

**Product Features**

**Operating Mode**  
Convertible: Ducted / Recirculating

**Number of speed settings**

**Delay Shut off modes**

10

**Silence level (dBA)**

**Required accessories**

**Optional accessories**

FF900056, KF900055

**Number of lights**

1

**Type of lamps used**

Fluorescent

**Total power of the lamps (W)**

36

**Grease filter material**

Washable aluminium

**Grease filter type**

Multilayer

**Clean filter reminders**

**Consumption and connection features**

**UPC code**

825225816171

**Material**

Stainless steel

**Watts (W)**

250

**Current (A)**

3

**Volts (V)**

120

**Frequency (Hz)**

60

**Approval certificates**

ETL

**Power cord length (in)**

47 3/16 "

**Power cord length (cm)**

120

**Plug type**

120V-3 prong

**Overall appliance dimensions (HxWxD)**

(in)

17 " / 17 " x 23 1/2 " x

**Overall appliance dimensions (HxWxD)**

(mm)

431 MM x 598 x 304

**Product packaging dimensions**

(HxWxD) (in)

15.35 x 25.59 x 21.25

**Product packaging dimensions**

(HxWxD) (mm)

390 x 650 x 540

**Adjustable feet**

**Height of the chimney (in)**

**Height of the chimney (mm)**

**Vertical rise height**

**Required distance above cooktop/  
ranges**

18 1/2 "/23 9/16 "

**Net weight (lbs)**

37

**Net weight (kg)**

16.607

**Gross weight (lbs)**

43

**Gross weight (kg)**

19.0

**Motor location**

Integrated motor in hood body

**Maximum CFM**

**Diameter of air duct (in) top**

**Diameter of air duct (in) back**

**Discharge direction**

**No-return airflow flap**

No

2019-09-24

Page 1

