



AH900791
90 cm flat screen hood for exhaust/
recirculating air operation

Stainless steel-colored handle strip
Technology concealed - design
revealed
Top performance with low noise -
optimum benefit with minimal sound
Eight-key operation - direct access to
all functions
Metal grease filter, dishwasher safe
7-inch pull-out steam visor
Front operation; handle strip not
replaceable
Bright cooking area illumination by
2x24 W compact fluorescent lamp
Three electronically controlled
speeds plus intensive mode
Delayed shut-off function
Special function: interval ventilation
Grease filter saturation indicator.
ø 6" exhaust air pipe
max. unobstructed airflow : 660 m³ /
h
Exhaust mode DIN EN 61591 : 600
m³ / h
Recirculation mode DIN EN 61591:
370 m³ / h
Noise level: 54 dB
Total rating : 260 W

Color Variants

AH900791

Product Features

Operating Mode

Convertible: Ducted / Recirculating

Number of speed settings

Delay Shut off modes

10

Silence level (dBA)

Required accessories

Optional accessories

FF900091, KF900090

Number of lights

2

Type of lamps used

Fluorescent

Total power of the lamps (W)

48

Grease filter material

Washable aluminium

Grease filter type

Multilayer

Clean filter reminders

Consumption and connection features

UPC code

825225816188

Material

Stainless steel

Watts (W)

260

Current (A)

5

Volts (V)

120

Frequency (Hz)

60

Approval certificates

ETL

Power cord length (in)

47 3/16 "

Power cord length (cm)

120

Plug type

120V-3 prong

**Overall appliance dimensions (HxWxD)
(in)**

17 " / 17 " x 35 5/16 " x

**Overall appliance dimensions (HxWxD)
(mm)**

431 MM x 898 x 304

**Product packaging dimensions
(HxWxD) (in)**

14.96 x 37.40 x 20.47

**Product packaging dimensions
(HxWxD) (mm)**

380 x 950 x 520

Adjustable feet

Height of the chimney (in)

Height of the chimney (mm)

Vertical rise height

**Required distance above cooktop/
ranges**

18 1/2 "/23 9/16 "

Net weight (lbs)

51

Net weight (kg)

22.967

Gross weight (lbs)

55

Gross weight (kg)

25.0

Motor location

Integrated motor in hood body

Maximum CFM

Diameter of air duct (in) top

Diameter of air duct (in) back

Discharge direction

No-return airflow flap

No

2019-09-24

Page 1

