



Color Variants

BX481612
Stainless steel-backed full glass door
Width 76 cm

Included accessories

x enamel baking tray.
suit. pyrolytic clean.
x rotary spit.
x grill shelf.
x grill tub with grid.
x pluggable meat probe.
x enamel baking tray.
suit. pyrolytic clean.
x rotary spit.
x grill shelf.
x grill tub with grid.
x pluggable meat probe.

Optional accessories

BA018165
Pull-out system
BA028115
Baking tray, enameled
BA038165
Wire rack, chromium-plated
BA058115
Heating element for baking stone and cast-iron roaster
BA058133
Baking stone
BS020002
Pizza peel, additional set of 2
GN340230

Product Variants

BX480612
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
right-hand
Controls centered

BX481612
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
left-hand
Controls centered

Pyrolytic system
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
Core temperature probe with estimation of cooking time
TFT touch display
Electronic temperature control from 30 °C to 300 °C
2 x 110 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Information key with use indicators.
Side-opening door opens up to 180° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.
Rotisserie spit (lower oven).
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
10 W halogen light on the side.
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
When planning a corner solution, pay attention to the 90° door opening angle.
The mains socket needs to be planned outside the built-in niche.

Connection

Total connected load 9.2 KW.
Total Amps: 40 A.
208 / 220 - 240 V / 60 Hz.
Connection cable 1.8 m without plug.

Product Features

Cooking mode

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

Cooking method second cavity

Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

Integrated Cleaning system

Number of interior lights

2

Included accessories

x enamel baking tray,suit. pyrolytic clean, x rotary spit, x grill shelf, x grill tub with grid, x pluggable meat probe

Bake Element Wattages cavity 1 (W)

1700

Broil Element Wattages cavity 1 (W)

3900

Convection Element Wattages cavity 1 (W)

Microwave Wattages (W)

Consumption and connection features

UPC code

825225957386

Product color

Alternative colors available

Energy source

Electric

Watts (W)

9200

Current (A)

40

Volts (V)

208/220-240

Frequency (Hz)

60

Approval certificates

CSA, ETL, UL

Power cord length (in)

70 7/8"

Power cord length (cm)

180.0

Appliance Dimensions (h x w x d) (cm)

142.8 x 75.2 x 54.7

Required cutout size (HxWxD) (in)

56 1/8 " x 28 1/2 " x 21 11/16 "

Overall appliance dimensions (HxWxD) (in)

56 1/4 " x 29 5/8 " x 21 9/16 "

Overall appliance dimensions (HxWxD) (mm)

1428 x 752 x 547

Product packaging dimensions (HxWxD) (in)

69.09 x 33.46 x 29.72

Product packaging dimensions (HxWxD) (mm)

1755 x 755 x 850

Net weight (kg)

161.820

Gross weight (lbs)

380.000

Gross weight (kg)

172.5

2020-09-03

Page 1

BX481612
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
left-hand
Controls centered
2020-09-03
Page 2

