



CM210710

Built-In Fully Automatic Coffee Machine 200 series

Stainless steel

CM210710

Aroma-Whirl brewing technology: full aroma
Single portion cleaning: 100 % hygiene
Immediate coffee brewing after foaming

Handling

8 language function display.
Programmable turn-on time and eco-function.
6 levels of ground coffee portioning from very mild to extra strong.
6 individual grinding level settings.
Serves 1 or 2 cups with selection of 12 water quantity levels.
Height adjustable coffee dispenser.
4 different water hardness settings.
3 different coffee temperature levels.

Features

215 psi thermo-block pressure pump system.
Conical grinding gear of hardened steel.
Adjustable brewing chamber from 0.25-0.5 oz (7 bis 14 g).
Removable 1.9 quarts (1.8 l) water tank.
Steam and hot water function.
Operation indicator.
Bean container with aroma preservation lid for up to 14 ounces (400 g).
Separate container for second ground coffee type.
Electronic fill level control for water and coffee beans.
Electronic fill level control for drip tray and container for coffee residue.
Fully automatic rinse programme when machine is turned on/off.
Automatic cleaning and descaling programme.

Planning notes

Ideal installation height 37 3/8 " or higher.
The door panel surface of the appliance extends 47 mm from the furniture cavity.
The cabinet must not have a rear panel behind the appliance.
Plan a venting gap of at least 200 cm².
Venting gaps and air intake must not be blocked.
Mount directly above 14 cm high warming drawer in 59 cm standard niche.

Connection

Total connected load 1.3 KW.
Total Amps: 40 A.
<200053val> / <200036val>
Connecting cable (118 ") with plug.

