

Color Variants RB280704 With fresh cooling Fully integrated

Included accessories

2 x cold accumulator. 2 x egg tray. 1 x ice cube tray.

RB280704

Fridge-freezer combination 200 series

With fresh cooling

Fully integrated

Niche width 56 cm, Niche height 177.5

3 climate zones incl. one fresh cooling drawer with manually adjustable humidity Height adjustable safety glass

shelves Door racks with aluminium profiles Innovative defrost technology: Reduced energy consumption due to new evaporator design - Faster defrosting and easier cleaning due to less severe and more uniform ice build-up - Safety glass shelf between freezer drawers

Cushioned door closing system allowing a soft and controlled door closure

Net volume 255 litres

Electronic temperature control with digital display. Touch keys.

Technical Features

Automatic defrosting with defrost water evaporation.

Cushioned door closing system from 20° door opening angle, integrated in door hinge.

Open-door and malfunction alarm. Home network integration for digital services (Home Connect) wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check; homeconnect.com.

Cooling

Fast cooling.

Temperature adjustable from +2 °C to +8 °C. 5 safety glass shelves, of which

1 is fully extendable and 4 height adjustable.

1 large door rack with aluminium profile for bottles with flexible bottle holder. 4 door racks with aluminium profile. Bright interior lighting with integrated glare-free side light elements. Net volume 188 litres.

Fresh cooling

1 full width fresh cooling drawer. Humidity can be adjusted manually. Ideal for fruit and vegetables.

Freezing

No-frost technology with fast freezing. Temperature adjustable from -16 °C to -24 °C.

4-star freezer compartment. Defrost assistance.

3 freezer drawers, 1 of which extra large.

2 safety glass shelves. Net volume 67 litres.

Consumption data

Energy consumption 394 kWh/year. Noise level 39 dB (re 1 pW).

Planning notes

Flat hinge

Door hinge right, reversible. Door opening angle of 115°, fixable at

Max. door panel weight: Upper door 18 kg. Lower door 18 kg.

Connection

Total connected load 0.120 KW. Connecting cable 2.3 m with plug. **Product Features**

Multi-Flow Air Tower

No

SUPERCOOL

SUPERFREEZE No

Temperature Controlled Drawer

Humidity Control Drawer

Number of Door Bins - Refrigerator

Adjustable Door Bins - Refrigerator

Tilt-Out Door Bins - Refrigerator

Gallon Storage

Gallon Storage Bins

Motorized Shelf

Adjustable Shelves - Refrigerator

Shelf Material - Refrigerator

Reversible Door Hinge

Yes

Lighting

Door Open Indicator

Yes

Drawers with telscopic rails

none

Ice Maker

No

Ice Storage Capacity (Ibs)

Ice Cubes per Day (lbs)

Consumption and connection features

825225924791

Variant color

Not applicable

Panel ready Not possible

Silence level (dBA)

Watts (W)

120

Current (A)

Volts (V)

110-120

Frequency (Hz)

Energy consumption (kWh/yr)

Energy Star® qualified

Approval certificates

Power cord length (in)

Plug type

120V-3 prong

Required cutout size (HxWxD) (in)

70" x 22 1/4" x 21 3/4

Appliance dimensions (h x w x d) inch

69 3/4" x 22" x 21 1/2"

Product packaging dimensions (HxWxD) (in)

72.44 x 24.40 x 25.19

Total unit gross capacity (cu. ft.) - AHAM

Refrigerator Gross capacity (cu. ft.)

Freezer Gross capacity (cu ft)

Net weight (lbs) 155.000

Gross weight (lbs)

167.000

2020-08-14



RB280704
Fridge-freezer combination 200 series
With fresh cooling
Fully integrated
Niche width 56 cm, Niche height 177.5

2020-08-14 Page 2





