



RF411705
Vario freezer 400 series
Fully integrated, with ice maker
Niche width 45.7 cm, Niche height 213.4 cm

Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front
2. Pull-to-open function to facilitate opening the door using a handle

The drawers in the RC and RF models are positioned at the same height. With side-by-side installation, the glass shelves and door racks can be aligned on the same level

Material and aesthetics of interior as for RC model

- Glass shelves
 - Solid anthracite aluminium door racks
- Flat stainless steel inner door, full-length

Almost invisible rail system for shelves and door racks for flexible positioning
Integrated ice maker with fixed inlet water connection
TFT touch display
Net volume 242 litres
Energy star qualified

Handling

TFT touch display operation.
Clear text display.

Technical Features

Dynamic cold air distribution.
Automatic defrosting with defrost water evaporation.
Cushioned door closing system.
Rest mode certified by Star-K.
When rest mode is active, the appliance can only be opened using a handle.
Open-door and malfunction alarm.
Home network integration for digital services (Home Connect) wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Freezing

No-frost technology with fast freezing at -30 °C.
Temperature adjustable from -16 °C to -24 °C.
4-star freezer compartment.
Freezing capacity 6.3 kg/24 h.
4 safety glass shelves, white glass, 3 of which are individually height adjustable.
2 fully extendable drawers with transparent front.
Flat door rail system with fully flexible positioning of door racks.
4 height-adjustable door racks.

Ice maker

Integrated in the freezer compartment, with fixed inlet water connection.
Particle filter for water inlet, integrated in ventilation grille area.
Can be switched off.

Product Features

UPC code

825225960911

Variant color

Not applicable

Panel ready

Installation Type

N/A

Silence level

42

Watts

350

Fuse protection

10

Volts

110-120

Frequency

60

Energy consumption

404.0

Energy Star® qualified

Yes

Approval certificates

CSA

Power cord length (in)

118,1"

Plug type

120V-3 prong

Appliance dimensions (h x w x d) inch

83 3/4 " x 17 3/4" x 24"

Required cutout size (HxWxD) (in)

84" x 18" x 24 3/4"

Appliance Width (in)

17 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Product packaging dimensions

(HxWxD)

88.97 x 21.45 x 29.33

Total unit gross capacity - AHAM

8.6

Net weight

277.000

Gross weight

307.000

Consumption and connection features

2021-12-23

Page 1

Ice cube production approx. 1.4 kg/24 h.

Removable ice storage container with approx. 2.5 kg capacity.

Consumption data

Energy consumption 404 kWh/year.

Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.

Door hinge left, reversible.

Door opening angle of 115°, fixable at 90°.

For installation with a door opening angle of 90° the ice storage container must be exchanged for the small ice storage container (RA 448220). This must be done prior to fixing the door.

Max. door panel weight 55 lbs (25 kg).

Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 0.8 MPa (8 bar), connect pressure relief valve between water tap and hose set.

Connection

Total connected load 0.350 KW.

Total Amps: 10 A.

Connecting cable 118" (3.0 m), detachable.

Water inlet.

Supply hose length 1.3 m mit 3/4" connection.

Water pressure 2 to 8 bar.

Color Variants

RF411705

Included accessories

- 1 x ice cube scoop.
- 1 x connection set.
- 1 x Ice storage container. large.

Optional accessories

RA448220

Installation Accessories

RA421115

Stainless steel door panel with handle

RA423140

RA425110

Handle bar, stainless steel, long

RA428115

RA460012

RA460020

Connecting element for vertically split appliance fronts (for a flush front)

RA464113

Ventilation grille stainless steel

