



Color Variants

AC231120
Stainless steel and glass
Width 120 cm

AC231120
Ceiling ventilation 200 series
Stainless steel and glass
Width 120 cm
Air recirculation

Easy and time saving installation directly on the ceiling
Rim extraction with flat and easy-to-clean glass cover
Dimmable, indirect LED light

Output

Performance and noise level, output level 3/Intensive: Air output according to DIN EN 61591. Sound power level according to EN 60704-3. Sound pressure level according to EN 60704-13.

Air recirculation: 780 / 850 m³/h. 70 / 72 dB (A) re 1 pW. 56 / 58 dB (A) re 20 µPa.

Features

Three electronically controlled power levels and an intensive mode. Remote control is included in delivery. Interval ventilation, 10 min. Run-on function, 6 min. Grease filter saturation indicator. Metal grease filter, dishwasher-safe. Activated charcoal filter fitted in appliance ex factory. Activated charcoal filter saturation indicator. Activated charcoal filter regenerable up to four times. Stainless steel housing and glass filter cover in Gaggenau Silver. Indirect LED light (4000 K), dimmable. Lamp output 2 x 6W LED. Illuminance: 14 lx
2 high-performance fans.

Product rating

Sound level min. 57 dB / max. 70 dB normal mode.

Planning notes

Installation directly on the ceiling. A suitable load-bearing substructure is required for securing the extractor hood. Never fit the appliance directly onto plasterboard or similar lightweight construction materials. Note the position of the electrical outlet. Recommended minimum gap between filter openings and wall: 50 cm. Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm). Clearance above electric appliances min. 55 cm. Maximum clearance above cooktops 150 cm. Appliance weight: approx. 41.

Connection

Total connected load 192 W. Plan a connection cable.

Characteristics

Product name/family
Color chimney
Typology
Traditional
Approval certificates
Australia Standards, CE, G-Mark
Length of electrical supply cord (cm)
0
Required niche size for installation (HxWxD)
Height of the chimney (mm)
Height of product, without chimney (mm)
Minimum distance above an electric hob
550
Minimum distance above a gas hob
650
Net weight (kg)
40.526
Type of control
Electronic
Number of speed settings
Maximum output air extraction (m³/h)
Boost position output recirculating (m³/h)
850.0
Maximum output recirculating air (m³/h)
Boost position air extraction (m³/h)
Number of lights (Stck)
2
Noise level (dB(A) re 1 pW)
70
Diameter of air outlet (mm)
150
Grease filter material
Washable aluminium
EAN code
4242006261733

Consumption and connection features

Connection rating (W)
192
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
no plug
Installation type
Built-in

created on 2020-09-28
Page 1

