



Color Variants

AI240190
stainless steel with stainless steel
control panel
Width 90 cm

Installation Accessories

AD220396
Ceiling collar for air ducts
Stainless steel

AI240190
Island hood 200 series
stainless steel with stainless steel
control panel
Width 90 cm
Air extraction/recirculation

Timeless, elegant design
Highly efficient extraction of cooking
vapours
Energy-saving, low-noise fan
Patented filter technology with high
level of grease absorption
Rim extraction filter with flat and
easy-to-clean stainless steel
underside
Function for automatic, sensor-
controlled power adjustment
depending on the build-up of cooking
vapours
Dimmable LED light for illumination
of the whole cooktop
Air extraction or recirculation system
Recirculation module with activated
charcoal filter: Silent and highly
efficient air recirculation solution
with odour reduction comparable to
air extraction and long replacement
intervals

Output

Performance and noise level, output
level 3/Intensive:
Air output according to DIN EN 61591.
Sound power level according to EN
60704-3.
Sound pressure level according to EN
60704-13.
Air extraction:
620 / 850 m³/h.
62 / 69 dB (A) re 1 pW.
48 / 55 dB (A) re 20 µPa.
Air recirculation:
480 / 570 m³/h.
68 / 72 dB (A) re 1 pW.
54 / 58 dB (A) re 20 µPa.
95% odour reduction.

Features

Three electronically controlled power
levels and an intensive mode.
Automatic function with sensor-
controlled run-on function.
Grease filter saturation indicator.
Patented rim extraction filter,
dishwasher-safe.
Warm white LED light (3600 K),
dimmable.
Fan technology with highly efficient,
brushless DC motor.
Airflow-optimised interior for efficient
air circulation.
Easy mounting system for simple
installation and alignment.

Planning notes

The package includes the mounting
kit and the two-part chimney with
the dimensions from 674 mm to 854
mm. Individual planning solutions
can be implemented using the
special accessory chimney extension
AD200326 in combination with
mounting kit extension AD223346.
Special chimney types are available
upon request.
Clearance above gas appliances min.
65 cm (more than total load gas 12 kW
min. 70 cm).
Clearance above electric appliances
min. 55 cm.
The recirculation module with activated
charcoal filter can be installed on the
telescopic chimney.
When installing a ventilation hood with
air extraction mode and a chimney-
vented fireplace, the hood's power
supply line needs a suitable safety
switch.

Connection

Total connected load 280 W.
Connecting cable 1.3 m with plug.

Characteristics

Product name/family
Color chimney
Typology
Chimney
Approval certificates
Australia Standards, CE, Eurasian, G-
Mark, Ukraine, VDE
Length of electrical supply cord (cm)
130
Required niche size for installation
(HxWxD)
Height of the chimney (mm)
674-854
Height of product, without chimney
(mm)
70
Minimum distance above an electric
hob
550
Minimum distance above a gas hob
650
Net weight (kg)
33.767
Type of control
Electronic
Number of speed settings
Maximum output air extraction (m³/h)
620
Boost position output recirculating
(m³/h)
570.0
Maximum output recirculating air (m³/
h)
Boost position air extraction (m³/h)
850
Number of lights (Stck)
4
Noise level (dB(A) re 1 pW)
62
Diameter of air outlet (mm)
150 / 120
Grease filter material
Washable stainless steel
EAN code
4242006234638

Consumption and connection features

Connection rating (W)
280
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50; 60
Plug type
Gardy plug w/ earthing
Installation type
Island

created on 2020-02-19
Page 1

GAGGENAU