



AR400143
Remote fan unit
Metal housing
Max. air output 1005 m³/h
Air extraction/recirculation
Installation in the chimney of AI/AW 442

Powerful remote fan unit to combine with motorless appliances
Efficient BLDC technology
Compact, space-saving installation in the chimney of AI/AW 442

Output

Air output according to EN 61591 - max. 1005 m³/h.
Sound power level depends on the built-in situation.
Power levels depend on the motorless appliances

Features

3 electronically controlled power levels and one intensive mode.
Fan technology with highly efficient, brushless DC motor (BLDC).
Including sound insulation to minimise the noise level.
Metal housing, zinc-plated.
Pipe connection pieces on output side: 1x NW 150 round.

Planning notes

Remote fan unit in combination with the motorless AI/AW 442.
Connection to the respective appliances via network cable.
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Total connected load 230 W.
Connecting and network cable included in delivery.

Characteristics

Dimensions

Dimensions of the packed product

(HxWxD)

310 x 370 x 475

Dimensions of the master case (mm)

Pallet dimensions

170.0 x 80.0 x 120.0

Quantity per packing unit

Standard number of units per pallet

20

Units per layer

Net weight

6.5

Gross weight

6.8

EAN code

4242006239954

Maximum Power

Voltage

Frequency

Length of electrical supply cord

Plug type

Approval certificates

Consumption and connection features

created on 2022-08-11

Page 1

Color Variants

AR400143

Metal housing

Max. air output 1005 m³/h

AR400143
Remote fan unit
Metal housing
Max. air output 1005 m³/h
Air extraction/recirculation
Installation in the chimney of AI/AW 442
created on 2022-08-11
Page 2

