



AR401142

Optional accessories

AA400510:

Window contact switch with cable

Installation accessories

AD702052:

Exhaust air pipe dia. 200mm

Remote fan unit 400 series

AR401142

- Powerful remote fan unit to combine with motorless appliances
- Efficient BLDC technology
- Sound power level depends on the built-in situation.
- Power levels depend on the motorless appliances
- 3 electronically controlled power levels and one intensive mode.
- Powerful remote fan unit to combine with motorless appliances

Efficient BLDC technology

Output

Sound power level depends on the built-in situation.

Power levels depend on the motorless appliances

Features

3 electronically controlled power levels and one intensive mode.

Fan technology with highly efficient, brushless DC motor (BLDC).

Including sound insulation to minimise the noise level.

Stainless steel housing.

Pipe connection pieces on intake side: 1x NW 200 round.

Retaining bracket for installation on an outside wall enclosed.

Planning notes

Remote fan unit in combination with motorless appliances.

Connection to the respective appliances via network cable.

Acceptable temperature range for installation of the control box: -25 to 60 °C.

Distance for free air space from ground (or other object) to center of the pipe: min 60 cm.

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Total connected load 180 W.

Connecting cable 1.8 m, pluggable.

Network cable 5 m.

Air output according to EN 61591 - max. 950 m³/h.

