



AW240190
Wall-mounted hood 200 series
stainless steel with stainless steel
control panel
Width 90 cm
Air extraction/recirculation

Timeless, elegant design
Highly efficient extraction of cooking vapours
Energy-saving, low-noise fan
Patented filter technology with high level of grease absorption
Rim extraction filter with flat and easy-to-clean stainless steel underside
Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours
Dimmable LED light for illumination of the whole cooktop
Air extraction or recirculation system
Recirculation module with activated charcoal filter: Silent and highly efficient air recirculation solution with odour reduction comparable to air extraction and long replacement intervals

Output

Performance and noise level, output level 3/Intensive:
Air output according to DIN EN 61591.
Sound power level according to EN 60704-3.
Sound pressure level according to EN 60704-13.
Air extraction:
610 / 810 m³/h.
66 / 72 dB (A) re 1 pW.
52 / 58 dB (A) re 20 µPa.
Air recirculation:
450 / 530 m³/h.
70 / 74 dB (A) re 1 pW.
56 / 60 dB (A) re 20 µPa.
95% odour reduction.

Features

Three electronically controlled power levels and an intensive mode.
Automatic function with sensor-controlled run-on function.
Grease filter saturation indicator.
Patented rim extraction filter, dishwasher-safe.
Warm white LED light (3600 K), dimmable.
Fan technology with highly efficient, brushless DC motor.
Airflow-optimised interior for efficient air circulation.
Easy mounting system for simple installation and alignment.

Planning notes

The package includes the two-part chimney with the dimensions from 582 mm to 884 mm. Individual planning solutions can be implemented using the special accessory chimney extension AD200322 or by shortening the lower edge of the telescopic chimney. Special chimney types are available upon request.
Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).
Clearance above electric appliances min. 55 cm.
The recirculation module with activated charcoal filter can be installed on the external chimney or telescopic chimney. When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.

Connection

Total connected load 275 W.

Characteristics

Product name/family
Color chimney
Typology
Chimney
Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (cm)
130
Required niche size for installation (HxWxD)
Height of the chimney (mm)
582-884
Height of product, without chimney (mm)
70
Minimum distance above an electric hob
550
Minimum distance above a gas hob
650
Net weight (kg)
22.063
Type of control
Electronic
Number of speed settings
Maximum output air extraction (m³/h)
610
Boost position output recirculating (m³/h)
530.0
Maximum output recirculating air (m³/h)
Boost position air extraction (m³/h)
810
Number of lights (Stck)
3
Noise level (dB(A) re 1 pW)
66
Diameter of air outlet (mm)
120 / 150
Grease filter material
Washable stainless steel
EAN code
4242006234621

Consumption and connection features

Connection rating (W)
275
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
60; 50
Plug type
Gardy plug w/ earthing
Installation type
Wall-mounted

created on 2020-02-19
Page 1

Connecting cable 1.3 m with plug.

Color Variants

AW240190
stainless steel with stainless steel
control panel
Width 90 cm