



Color Variants

AW251172 Full glass front in Gaggenau metallic Width 70 cm
AW250172 Full glass front in Gaggenau anthracite Width 70 cm
AW253172 Full glass front in Gaggenau silver Width 70 cm

AW251172
Wall-mounted hood 200 series
Full glass front in Gaggenau metallic
Width 70 cm
Air extraction/recirculation
Delivery without chimney

Angled vapour screen provides particularly generous free space above the cooktop
Filter cover with easy to clean glass front
Glass cover fitting to oven 200 series
Energy-saving, low-noise fan
Vapours can be caught efficiently thanks to two suction areas on the underside and front
The glass panel can be extended forward to increase the area for catching vapours during particularly intensive cooking
Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours
Dimmable ambient lighting allows light to be adjusted individually
Air extraction or recirculation system

Output

Performance and noise level, output level 3/Intensive:
Air output according to DIN EN 61591.
Sound power level according to EN 60704-3.
Sound pressure level according to EN 60704-13.
Air extraction:
530 / 970 m³/h.
57 / 70 dB (A) re 1 pW.
43 / 56 dB (A) re 20 µPa.
Air recirculation:
470 / 680 m³/h.
68 / 78 dB (A) re 1 pW.
54 / 64 dB (A) re 20 µPa.
95% odour reduction.

Features

Three electronically controlled power levels and an intensive mode.
Automatic function with sensor-controlled run-on function.
Grease filter and activated charcoal filter saturation indicator.
Interval ventilation, 6 min.
Cooktop-based ventilation control (with suitable cooktop).
Integrated WiFi module for digital services (Home Connect).
The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com
Metal grease filter, dishwasher-safe.
Glass filter cover in Gaggenau metallic.
2 activated charcoal filter fitted in appliance ex factory.
Neutral white LED light (3500 K), continuously dimmable.
Lamp output 2 x LM5-01_LED_3W.
Illuminance: 440 lx
Indirect LED light (3.000 K), dimmable.
Fan technology with highly efficient, brushless DC motor.
Integrated sound insulation for quiet operation.
Easy to clean inner frame.
Easy mounting system for simple installation and alignment.

Product rating

Energy efficiency class A+.

Characteristics
Product name/family
Color chimney
Typology Chimney
Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (cm) 130
Required niche size for installation (HxWxD)
Height of the chimney (mm)
Height of product, without chimney (mm) 452
Minimum distance above an electric hob 450
Minimum distance above a gas hob 600
Net weight (kg) 21.491
Type of control Electronic
Number of speed settings
Maximum output air extraction (m³/h) 529
Boost position output recirculating (m³/h) 670.0
Maximum output recirculating air (m³/h)
Boost position air extraction (m³/h) 990
Number of lights (Stck) 2
Noise level (dB(A) re 1 pW) 57
Diameter of air outlet (mm) 150
Grease filter material Washable aluminium
EAN code 4242006264543
Consumption and connection features
Connection rating (W) 270
Current (A) 10
Voltage (V) 220-240
Frequency (Hz) 60; 50
Plug type Gardy plug w/ earthing
Installation type Wall-mounted

created on 2020-04-02

Page 1

Energy consumption xxx.
Ventilation efficiency class A.
Illumination efficiency class A.
Grease filter efficiency class B.
Sound level min. 42 dB / max. 57 dB normal mode.

Planning notes

The ventilation appliance is supplied for air recirculation mode only without a chimney. The special accessory AD 200 012 is available for potential air extraction mode.
Clearance above gas appliances min. 60 cm (more than total load gas 12 kW min. 70 cm).
Clearance above electric appliances min. 45 cm.
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.

Connection

Total connected load 270 W.
Connecting cable 1.3 m with plug.
Power consumption standby/display off 0.5 W.
Power consumption standby/network 2 W.
Please check the user manual for how to switch off the WiFi module.