

Color Variants

BO471101

Full glass door in Gaggenau Anthracite Width 60 cm

BO471111

Stainless steel-backed full glass door Width 60 cm

Included accessories

2 x enamel baking tray. suit. pyrolitic clean.

- 1 x rotary spit.
- 1 x glass pan.
- 1 x grill shelf.
- 1 x grill tub with grid.
- 1 x pluggable meat probe.

Optional accessories

BA026115

Baking tray, enamelled

BA046115

Glass tray

BA056133

Baking stone BS020002

Pizza paddle, set of 2

GN340230

Gastronorm roaster in cast aluminium

Product Variants BO470101

Oven 400 series

Full glass door in Gaggenau Anthracite Width 60 cm

controls at the top

BO471101 Oven 400 series

Full glass door in Gaggenau Anthracite

Width 60 cm

controls at the top

Handleless door / automatic door opening

Pyrolytic system

17 heating methods, with core temperature probe, rotisserie spit and baking stone function

TFT touch display Panel-free appliance with surface control module

Electronic temperature control from 30 °C to 300 °C

76 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

Handling

Automatic door opening. Rotary knob and TFT touch display operation.

Option to save individual recipes (incl. core temperature probe).

Information key with use indications. Side-opening door opens up to 180° angle.

Features

Core temperature probe with automatic shut-off.

Rotisserie spit.

Baking stone socket.

Actual temperature display.

Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term

60 W halogen light on the top. 2 x 10 W halogen light on the side. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing. Child lock.

Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Pvrolvtic system. Gaggenau enamel. Heated air cleaning catalyser.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 47 mm from the furniture cavity.

If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.

Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front

Anthracite

Construction type

Built-in Integrated Cleaning system

Pyrolytic Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm)

595 x 590 x 547 Dimensions of the packed product

(HxWxD) (mm)

780 x 760 x 680

Control Panel Material

Door Material Glass

Net weight (kg)

60.659

Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material

Oven control

electronic

Number of interior lights

Approval certificates

Australia Standards, CE, Eurasian,

Ukraine, VDE Length of electrical supply cord (cm)

EAN code 4242006249663

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle

conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection rating (W)

Current (A)

Voltage (V)

Frequency (Hz)

220-240

Plug type

no plug

created on 2020-08-01

Page 1



Total connected load 3.7 KW. Plan a connection cable.



BO471101 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm controls at the top

created on 2020-08-01 Page 2







