

Color Variants BO480111 Stainless steel-backed full glass door Width 76 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x rotary spit. 1 x grill shelf. 1 x grill tub with grid. 1 x pluggable meat probe.

Optional accessories BA018105 Pull-out system BA028115 Baking tray, enamelled BA038105 Wire rack, chromium-plated BA058115 Heating element for baking stone and Gastronorm roaster BA058133 Baking stone BS020002 Pizza paddle, set of 2 GN340230 Gastronorm roaster in cast aluminium

Product Variants BO481111 Oven 400 series Stainless steel-backed full glass door Width 76 cm controls at the top

BO480111

Oven 400 series Stainless steel-backed full glass door Width 76 cm controls at the top

Handleless door / automatic door opening Pyrolytic system 17 heating methods, with core temperature probe, rotisserie spit and baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C 110 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

Handling

Automatic door opening. Rotary knob and TFT touch display operation. Option to save individual recipes (incl. core temperature probe). Information key with use indications. Side-opening door opens up to 180° angle.

Features

Core temperature probe with automatic shut-off. Rotisserie spit. Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. 2 x 10 W halogen light on the side. Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning Pyrolytic system. Gaggenau enamel. Heated air cleaning catalyser.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 47 mm from the furniture cavity. If the handle (optional accessory)

is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.

Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front Stainless steel Construction type Built-in Integrated Cleaning system Pvrolvtic Required niche size for installation (HxWxD) 665-665 x 724-724 x 550 Dimensions of the product (mm) 670 x 752 x 547 Dimensions of the packed product (HxWxD) (mm) 860 x 760 x 850 Control Panel Material Door Material Stainless steel behind glass Net weight (kg)

78.611 Usable volume of cavity (I) 110

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material Oven control electronic

Number of interior lights

Approval certificates

Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE Length of electrical supply cord (cm) EAN code

4242006242220

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1.53

Energy consumption gas oven per cycle conventional (2010/30/EC) Energy consumption per cycle forced

air convection (2010/30/EC) 0.96

Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC)

Connection rating (W) 5520

Current (A) 25

Voltage (V) 220-240

Frequency (Hz) 50

Plug type fixed connection, no plug

created on 2020-07-28 Page 1





Connection

Total connected load 5.5 KW. Plan a connection cable.

BO480111 Oven 400 series Stainless steel-backed full glass door Width 76 cm controls at the top created on 2020-07-28 Page 2







When installed next to each other

