

Color Variants

BO481111

Stainless steel-backed full glass door Width 76 cm

Included accessories

- 1 x enamel baking trav. suit. pyrolitic clean.
- 1 x rotary spit.
- 1 x grill shelf.
- 1 x arill tub with arid.
- 1 x pluggable meat probe.

Optional accessories

BA018105

Pull-out system

BA028115

Baking tray, enamelled

BA038105

Wire rack, chromium-plated

BA058115

Heating element for baking stone and Gastronorm roaster

BA058133

Baking stone

BS020002

Pizza paddle, set of 2

GN340230

Gastronorm roaster in cast aluminium

Product Variants

BO480111 Oven 400 series Stainless steel-backed full glass door Width 76 cm controls at the top

BO481111 Oven 400 series

Stainless steel-backed full glass door

Width 76 cm

controls at the top

Handleless door / automatic door opening Pyrolytic system 17 heating methods, with core

temperature probe, rotisserie spit and baking stone function TFT touch display

Panel-free appliance with surface control module

Electronic temperature control from 30 °C to 300 °C

110 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

Handling

Automatic door opening. Rotary knob and TFT touch display operation.

Option to save individual recipes (incl. core temperature probe). Information key with use indications. Side-opening door opens up to 180°

Features

angle.

Core temperature probe with automatic shut-off.

Rotisserie spit.

Baking stone socket.

Actual temperature display. Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term

60 W halogen light on the top. 2 x 10 W halogen light on the side. Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing. Child lock.

Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Pvrolvtic system. Gaggenau enamel. Heated air cleaning catalyser.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 47 mm from the furniture cavity.

If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.

Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front

Stainless steel

Construction type

Built-in

Integrated Cleaning system

Pyrolytic

Required niche size for installation (HxWxD)

Connection

Total connected load 5.5 KW.

Plan a connection cable.

665-665 x 724-724 x 550

Dimensions of the product (mm) 670 x 752 x 547

Dimensions of the packed product (HxWxD) (mm)

860 x 760 x 850

Control Panel Material

Door Material

Stainless steel behind glass

Net weight (kg)

79,161

Usable volume of cavity (I)

110

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material

Oven control

electronic

Number of interior lights

Approval certificates

Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (cm)

EAN code

4242006242237

Consumption and connection features

Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC)

Connection rating (W)

Current (A)

Voltage (V)

220-240 Frequency (Hz)

Plug type

fixed connection, no plug


created on 2020-07-13

Page 1




BO481111 Oven 400 series Stainless steel-backed full glass door Width 76 cm controls at the top

created on 2020-07-13 Page 2







Cross section of the top/bottom door edge gaps



