



Color Variants

| |
|--|
| BOP210131 |
| Full glass door in Gaggenau Silver |
| Width 60 cm |
| BOP210101 |
| Full glass door in Gaggenau Anthracite |
| Width 60 cm |
| BOP210111 |
| Full glass door in Gaggenau Metallic |
| Width 60 cm |

Included accessories

| |
|-------------------------|
| 1 x enamel baking tray. |
| suit. pyrolytic clean. |
| 1 x grill shelf. |
| 1 x grill tub. |

Optional accessories

| |
|------------------------|
| BA056130 |
| Baking stone |
| BS020002 |
| Pizza paddle, set of 2 |

Product Variants

| |
|------------------------------------|
| BOP211131 |
| Oven 200 series |
| Full glass door in Gaggenau Silver |
| Width 60 cm |
| Left-hinged |

| |
|------------------------------------|
| BOP210131 |
| Oven 200 series |
| Full glass door in Gaggenau Silver |
| Width 60 cm |
| Right-hinged |

Flush installation
9 heating methods, with baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 50 °C to 300 °C
76 litres net volume
Energy efficiency class A

Heating methods

| |
|--------------------------------------|
| Hot air. |
| Eco hot air. |
| Top + bottom heat. |
| Top heat. |
| Bottom heat. |
| Hot air+ bottom heat. |
| Full surface grill + circulated air. |
| Full surface grill. |
| Baking stone function. |

Handling

Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Option to save individual recipes.
Information key with use indications.
Side-opening door opens up to 110° angle.

Features

Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
Chromium-plated side shelf supports with 4 tray levels.

Safety

Thermally insulated door with triple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Gaggenau enamel.
Heated air cleaning catalyser.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Connection

| |
|---|
| Characteristics |
| Color / Material Front |
| Aluminium |
| Construction type |
| Built-in |
| Integrated Cleaning system |
| No |
| Required niche size for installation (HxWxD) |
| 590-590 x 560-560 x 550 |
| Dimensions of the product (mm) |
| 595 x 590 x 547 |
| Dimensions of the packed product (HxWxD) (mm) |
| 780 x 760 x 680 |
| Control Panel Material |
| without panel |
| Door Material |
| Glass |
| Net weight (kg) |
| 51.321 |
| Usable volume of cavity (l) |
| 76 |
| Cooking method |
| Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot air and 1/1 bottom heating, Hot Air-Eco, Hot air grilling, Top heat |
| First cavity material |
| Enamelled |
| Temperature control |
| electronic |
| Number of interior lights |
| 1 |
| Approval certificates |
| Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE |
| Length of electrical supply cord (cm) |
| EAN code |
| 4242006242817 |

Consumption and connection features

| |
|---|
| Number of cavities (2010/30/EC) |
| 1 |
| Energy efficiency class (2010/30/EC) |
| A |
| Energy consumption per cycle conventional (2010/30/EC) |
| 1.25 |
| Energy consumption gas oven per cycle conventional (2010/30/EC) |
| Energy consumption per cycle forced air convection (2010/30/EC) |
| 0.83 |
| Energy consumption gas oven per cycle forced air convection (2010/30/EC) |
| Energy efficiency index (2010/30/EC) |
| 95.4 |
| Connection rating (W) |
| 3700 |
| Current (A) |
| 16 |
| Voltage (V) |
| 220-240 |
| Frequency (Hz) |
| 50; 60 |
| Plug type |
| fixed connection, no plug |

created on 2019-09-24

Page 1

Energy efficiency class A.
Total connected load 3.7 kW.
Plan a connection cable.

GAGGENAU

BOP210131
Oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
Right-hinged

created on 2019-09-24
Page 2

