



BOP210132
Oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
right-hinged



Flush installation
 9 heating methods, with baking stone function
 TFT touch display
 Panel-free appliance with surface control module
 Electronic temperature control from 50 °C to 300 °C
 76 litres net volume

Heating methods

Hot air.
 Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling

Rotary knob and TFT touch display operation.
 Clear text display.
 Option to save individual recipes. Information key with use indications. Side-opening door opens up to 110° angle.

Features

Baking stone socket.
 Actual temperature display.
 Rapid heating.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).
 60 W halogen light on the top.
 Enamelled wire racks on the side with 4 rack levels.

Selected digital services (Home Connect)

Remote control and monitoring. Recipes.
 Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
 The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Thermally insulated door with triple glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning

Gaggenau enamel.
 Heated air cleaning catalyser.

Planning notes

Door hinge not reversible.
 The door panel surface of the appliance extends 21 mm from the furniture cavity.
 The outer edge of the door handle extends 72 mm from the furniture cavity.
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the side-opening door and the minimum required distance to the wall.

Characteristics

Color / Material Front
Construction type
 Built-in
Integrated Cleaning system
 No
Min. required niche size for installation (HxWxD)
 590-590 x 560-560 x 550
Dimensions
 595 x 590 x 547
Dimensions of the packed product (HxWxD)
 770 x 710 x 660
Control Panel Material
 without panel
Door Material
 Glass
Net weight
 52.5
Usable volume of cavity
 76
Cooking method
 Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat
First cavity material
Oven control
 electronic
Number of interior lights
 1
Length of electrical supply cord
EAN code
 4242006279820
Number of cavities (2010/30/EC)
 1
Energy efficiency rating
 A
Energy consumption per cycle conventional (2010/30/EC)
 1.25
Energy consumption gas oven per cycle conventional (2010/30/EC)
 0.83
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
 0.83
Energy consumption per cycle forced air convection (2010/30/EC)
 0.83
Energy efficiency index (2010/30/EC)
 95.4
Connection rating
 3700
Fuse protection
 16
Voltage
 220-240
Frequency
 50-60
Plug type
 fixed connection, no plug (electrical connection by electrician)
Included accessories
 1 x enamel baking tray, suit. pyrolytic clean, 1 x grill shelf, 1 x grill tub

Consumption and connection features

created on 2023-05-08
 Page 1

Color Variants

BOP210132
Full glass door in Gaggenau Silver
Width 60 cm
BOP210102
Full glass door in Gaggenau Anthracite
Width 60 cm
BOP210112
Full glass door in Gaggenau Metallic
Width 60 cm

Included accessories

1 x enamel baking tray.
 suit. pyrolytic clean.
 1 x grill shelf.
 1 x grill tub.

Optional accessories

BA036102
Wire rack, chromium-plated
BA046117
Glass tray
BA056115
Heating element for baking stone and Gastronorm roaster
BA056130
Baking stone
BA216102
Quadruple telescopic pull-out rack
BA226102
Grill tray, enamelled
BA226112
Baking tray, enamelled
BS020002
Pizza paddle, set of 2

Product Variants

BOP211132
Oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
left-hinged

For installation underneath cooktops:
 Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The main socket needs to be planned outside of the niche.

The LAN port can be found at the back on the upper right side.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 KW.

Plan a connection cable.

Power consumption standby/display on 0.7 W.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.4 W.

Time auto-standby/display on 20 min.

Time auto-standby/display off 20 min.#

Time auto-standby/network 20 min.

Plan a LAN cable.

