



Color Variants

BOP220111
Full glass door in Gaggenau Metallic
Width 60 cm

Optional accessories

BA026115
Baking tray, enamelled
BA046115
Glass tray
BA056133
Baking stone
BA226105
Grill tray, enamelled
BS020002
Pizza paddle, set of 2
GN340230
Gastronorm roaster in cast aluminium

BOP220111
Oven 200 series
Full glass door in Gaggenau Metallic
Width 60 cm

Flush installation
Pyrolytic system
9 heating methods, with baking stone function
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 50 °C to 300 °C
76 litres net volume

Heating methods

Hot air, Eco hot air, Top + bottom heat, Top heat, Bottom heat, Hot air+ bottom heat, Full surface grill + circulated air, Full surface grill, Baking stone function.

Handling

Rotary knob and TFT touch display operation.
Option to save individual recipes. Information key with use indications. Side-opening door opens up to 110° angle.

Features

Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated air cleaning catalyser.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Connection

Total connected load 3.7 KW.
Plan a connection cable.

Characteristics

Color / Material Front
Stainless steel
Construction type
Built-in
Integrated Cleaning system
Pyrolytic
Required niche size for installation (HxWxD)
590-590 x 560-560 x 550
Dimensions
595 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
780 x 760 x 680
Control Panel Material
Door Material
Glass
Net weight (kg)
54.904
Usable volume of cavity (l)
76
Cooking method
Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat
First cavity material
Temperature control
electronic
Number of interior lights
1
Approval certificates
Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (cm)
EAN code
4242006240530

Consumption and connection features

Number of cavities (2010/30/EC)
1
Energy efficiency rating
A
Energy consumption per cycle conventional (2010/30/EC)
1.25
Energy consumption gas oven per cycle conventional (2010/30/EC)
Energy consumption per cycle forced air convection (2010/30/EC)
0.83
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
Energy efficiency index (2010/30/EC)
95.4
Connection rating (W)
3700
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug
created on 2020-10-09
Page 1

