



**BOP220132**  
**Oven 200 series**  
**Full glass door in Gaggenau Silver**  
**Width 60 cm**



Flush installation  
 Pyrolytic system  
 9 heating methods, with baking stone function  
 TFT touch display  
 Panel-free appliance with surface control module  
 Electronic temperature control from 50 °C to 300 °C  
 76 litres net volume

#### Heating methods

Hot air.  
 Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

#### Handling

Rotary knob and TFT touch display operation.  
 Clear text display.  
 Option to save individual recipes.  
 Information key with use indications.  
 Side-opening door opens up to 110° angle.

#### Features

Baking stone socket.  
 Actual temperature display.  
 Rapid heating.  
 60 W halogen light on the top.  
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.  
 Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.  
 The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: [www.home-connect.com](http://www.home-connect.com)

#### Safety

Thermally insulated door with quintuple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
 Gaggenau enamel.  
 Heated air cleaning catalyser.

#### Planning notes

Door hinge not reversible.  
 The door panel surface of the appliance extends 21 mm from the furniture cavity.  
 The outer edge of the door handle extends 72 mm from the furniture cavity.  
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.  
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 110° door opening angle.  
 For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

#### Characteristics

**Color / Material Front**  
**Construction type**  
 Built-in  
**Integrated Cleaning system**  
 Pyrolytic  
**Min. required niche size for installation (HxWxD)**  
 590-590 x 560-560 x 550  
**Dimensions**  
 595 x 590 x 547  
**Dimensions of the packed product (HxWxD)**  
 780 x 760 x 680  
**Control Panel Material**  
 without panel  
**Door Material**  
 Glass  
**Net weight**  
 55.0  
**Usable volume of cavity**  
 76  
**Cooking method**  
 Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat  
**First cavity material**  
**Oven control**  
 electronic  
**Number of interior lights**  
 1  
**Length of electrical supply cord**  
**EAN code**  
 4242006279882  
**Number of cavities (2010/30/EC)**  
 1  
**Energy efficiency rating**  
 A  
**Energy consumption per cycle conventional (2010/30/EC)**  
 1.25  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
 0.83  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
 0.83  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
 95.4  
**Energy efficiency index (2010/30/EC)**  
 95.4  
**Connection rating**  
 3700  
**Fuse protection**  
 16  
**Voltage**  
 220-240  
**Frequency**  
 50  
**Plug type**  
 fixed connection, no plug (electrical connection by electrician)

**Included accessories**  
 1 x enamel baking tray, suit. pyrolytic clean, 1 x glass pan, 1 x grill shelf

#### Consumption and connection features

created on 2023-01-26

Page 1

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.  
 The main socket needs to be planned outside of the niche.  
 The LAN port can be found at the back on the upper right side.

#### Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.  
 Total connected load 3.7 KW.  
 Plan a connection cable.  
 Power consumption standby/display on 0.7 W.  
 Power consumption standby/display off 0.5 W.  
 Power consumption standby/network 1.4 W.  
 Time auto-standby/display on 20 min.  
 Time auto-standby/display off 20 min.#  
 Time auto-standby/network 20 min.  
 Plan a LAN cable.

#### Color Variants

**BOP220132**  
**Full glass door in Gaggenau Silver**  
**Width 60 cm**  
**BOP220102**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**BOP220112**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**

#### Included accessories

1 x enamel baking tray.  
 suit. pyrolytic clean.  
 1 x glass pan.  
 1 x grill shelf.

#### Optional accessories

**BA016105**  
**Pull-out system**  
**BA026115**  
**Baking tray, enamelled**  
**BA036105**  
**Wire rack, chromium-plated**  
**BA046117**  
**Glass tray**  
**BA056115**  
**Heating element for baking stone and Gastronorm roaster**  
**BA056133**  
**Baking stone**  
**BA226105**  
**Grill tray, enamelled**  
**BS020002**  
**Pizza paddle, set of 2**  
**GN340230**  
**Gastronorm roaster in cast aluminium**

#### Product Variants

**BOP221132**  
**Oven 200 series**  
**Full glass door in Gaggenau Silver**  
**Width 60 cm**

