

Color Variants BOP240101 Full glass door in Gaggenau Anthracite Width 60 cm BOP240111 Full glass door in Gaggenau Metallic Width 60 cm BOP240131 Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf. 1 x pluggable meat probe.

Optional accessories BA026115 Baking tray, enamelled BA046115 Glass tray BA056133 Baking stone BA226105 Grill tray, enamelled BS020002 Pizza paddle, set of 2 GN340230 Gastronorm roaster in cast aluminium BOP240101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm

Flush installation 13 heating methods, with core temperature probe and baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C 76 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofina. Defrostina.

Handling

Rotary knob and TFT touch display operation.

Option to save individual recipes (incl. core temperature probe). Information key with use indications. Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off. Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. Chromium-plated side shelf supports with 4 trav levels.

Safety

Thermally insulated door with triple glazing. Child lock Safety shut-off. Cooled housing with temperature protection.

Cleaning

coating. Gaggenau enamel. Heated air cleaning catalyser. Grease filter in front of hot air fan.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture

cavity. Necessary lateral gap between

appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Characteristics Color / Material Front

Construction type

Integrated Cleaning system

590-590 x 560-560 x 550 Dimensions of the product (mm)

Required niche size for installation

Dimensions of the packed product

Anthracite

Built-in

(HxWxD)

595 x 590 x 547

(HxWxD) (mm)

Door Material

Net weight (kg)

Cooking method

First cavity material

Approval certificates

Number of interior lights

Oven control

electronic

EAN code

1.25

0.83

95 4

3700

16

Current (A)

Voltage (V)

Frequency (Hz) 50:60

fixed connection, no plug

created on 2020-07-31

220-240

Plug type

Page 1

4242006242602

Glass

51.754

76

780 x 760 x 680

Control Panel Material

Usable volume of cavity (I)

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough

proving setting, Full width grill, Half

grilling, Roaster function, Top heat

CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (cm)

Consumption and connection features

Energy efficiency class (2010/30/EC)

Energy consumption gas oven per cycle

Energy consumption per cycle forced

Energy consumption gas oven per cycle

forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Number of cavities (2010/30/EC)

Energy consumption per cycle

conventional (2010/30/EC)

conventional (2010/30/EC)

air convection (2010/30/EC)

Connection rating (W)

width grill, Hot Air, Hot Air-Eco, Hot air

No

Connection

Total connected load 3.7 KW. Plan a connection cable.



Back wall and ceiling with catalytic

BOP240101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm created on 2020-07-31 Page 2



