

Color Variants BOP240111 Full glass door in Gaggenau Metallic Width 60 cm BOP240101 Full glass door in Gaggenau Anthracite Width 60 cm BOP240131 Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf. 1 x pluggable meat probe.

Optional accessories BA026115 Baking tray, enamelled BA046115 Glass tray BA056133 Baking stone BA226105 Grill tray, enamelled BS020002 Pizza paddle, set of 2 GN340230 Gastronorm roaster in cast aluminium

Product Variants BOP241111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm BOP240111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm

Flush installation 13 heating methods, with core temperature probe and baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C 76 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

Handling

Rotary knob and TFT touch display operation. Option to save individual recipes (incl.

core temperature probe). Information key with use indications. Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off. Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. Chromium-plated side shelf supports with 4 tray levels.

Safety

Thermally insulated door with triple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Back wall and ceiling with catalytic coating. Gaggenau enamel. Heated air cleaning catalyser. Grease filter in front of hot air fan.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture

cavity. Necessary lateral gap between appliance door and furniture panel of

min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers

next to the appliance. When planning a corner solution, pay attention to the 110° door opening angle.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Characteristics Color / Material Front Stainless steel

Construction type

Integrated Cleaning system

590-590 x 560-560 x 550 Dimensions of the product (mm)

Required niche size for installation

Built-in

(HxWxD)

595 x 590 x 547

No

Total connected load 3.7 KW. Plan a connection cable.

Dimensions of the packed product (HXWxD) (mm) 780 x 760 x 680 Control Panel Material Door Material Glass Net weight (kg) 52.054 Usable volume of cavity (l) 76 Cooking method Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Eull width arill Half

proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat First cavity material

Oven control electronic

Number of interior lights

Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE Length of electrical supply cord (cm) EAN code 4242006242626

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1.25

Energy consumption gas oven per cycle conventional (2010/30/EC) Energy consumption per cycle forced

air convection (2010/30/EC) 0.83 Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC)

95.4 Connection rating (W) 3700

Current (A)

Voltage (V) 220-240

Frequency (Hz) 60: 50

Plug type

fixed connection, no plug created on 2020-07-31





BOP240111 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm created on 2020-07-31 Page 2



