

Color Variants

BOP250101

Full glass door in Gaggenau Anthracite Width 60 cm

BOP250111

Full glass door in Gaggenau Metallic Width 60 cm

BOP250131

Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean.

- 1 x glass pan.
- 1 x grill shelf.
- 1 x pluggable meat probe.

Optional accessories

BA026115

Baking tray, enamelled

BA046115

Glass tray BA056133

Baking stone

BA226105

Grill tray, enamelled

BS020002

Pizza paddle, set of 2

GN340230

Gastronorm roaster in cast aluminium

Product Variants

BOP251101 Oven 200 series

Full glass door in Gaggenau Anthracite Width 60 cm

BOP250101 Oven 200 series

Full glass door in Gaggenau Anthracite

Width 60 cm

Flush installation Pyrolytic system 13 heating methods, with core temperature probe and baking stone function

TFT touch display Panel-free appliance with surface control module

Electronic temperature control from 30 °C to 300 °C

76 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air+ bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function, Roaster function, Dough proofing. Defrosting.

Handling

Rotary knob and TFT touch display operation.

Option to save individual recipes (incl. core temperature probe). Information key with use indications. Side-opening door opens up to 110°

angle. **Features**

Core temperature probe with automatic shut-off.

Baking stone socket. Actual temperature display.

Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term

60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quintuple glazing. Child lock Safety shut-off.

Cooled housing with temperature

Cleaning

Pyrolytic system. Gaggenau enamel. Heated air cleaning catalyser.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front

Anthracite

Construction type

Built-in Integrated Cleaning system

Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions of the product (mm) 595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

780 x 760 x 680

Control Panel Material **Door Material**

Glass

Net weight (kg)

54,149

Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat

First cavity material

Oven control

Number of interior lights

Approval certificates

Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (cm)

EAN code

4242006242459

Consumption and connection features

Number of cavities (2010/30/EC)

Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC) 0.83

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection rating (W)

3700 Current (A)

Voltage (V) 220-240

Frequency (Hz)

50 Plug type

fixed connection, no plug

created on 2020-07-24

Page 1



Total connected load 3.7 KW. Plan a connection cable.

BOP250101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm

created on 2020-07-24 Page 2



