

Color Variants BSP220100 Full glass door in Gaggenau Anthracite Width 60 cm BSP220110 Full glass door in Gaggenau Metallic Width 60 cm BSP220130 Full glass door in Gaggenau Silver Width 60 cm

Optional accessories GN114130 Gastronorm insert, stainless steel, GN 1/3 GN114230 Gastronorm insert, stainless steel, GN 2/3 GN124130 Gastronorm insert, stainless steel, GN 1/3 GN124230 Gastronorm insert, stainless steel, GN 2/3 GN340230 Gastronorm roaster in cast aluminium

Product Variants BSP221100 Steam oven 200 Series Full glass door in Gaggenau Anthracite Width 60 cm Controls at the top

# BSP220100

Steam oven 200 Series Full glass door in Gaggenau Anthracite Width 60 cm Controls at the top

Flush installation Water tank Steaming without pressure with 100% humidity from 30 °C to 100 °C TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 100 °C

### Heating methods

100 % humidity. Slow steaming. Dough proofing. Defrosting. Regenerating. Low temperature steaming.

# Handling

Rotary knob and TFT touch display operation. Information key with use indications. Side-opening door opens up to 110° angle.

### Features

Removable 1.3 litre water tank. Water level warning. Actual temperature display. Electronic boiling point detection. 60 W halogen light on the side. Hygienic stainless steel cooking interior. 3 tray levels.

## Safety

Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning aid. Descaling programme.

#### Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture

cavity. Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 110° door opening

angle. To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

### Connection

Total connected load 1.9 KW. Connection cable 1.5 m without plug. Characteristics Color / Material Front Anthracite Construction type Built-in Door opening Lateral Required niche size for installation (HxWxD) Dimensions 455 x 590 x 547 Dimensions of the packed product (HxWxD) (mm) 575 x 660 x 690 Control Panel Material Door Material Glass Net weight (kg) 34.308 Approval certificates CCC, CE, China, China ROHS 20, Ukraine, VDE Length of electrical supply cord (cm) 150

EAN code 4242006217402 Connection rating (W) 1900

Current (A)

#### Voltage (V) 220-240

Ukraine, VDE

Frequency (Hz) 50; 60 Plug type fixed connection, no plug Approval certificates CCC, CE, China, China ROHS 20,

Consumption and connection features created on 2021-04-07 Page 1



BSP220100 Steam oven 200 Series Full glass door in Gaggenau Anthracite Width 60 cm Controls at the top created on 2021-04-07 Page 2





