



Color Variants

BSP220101
BSP220111
BSP220131

Included accessories

1 x grid.
1 x STS tray.
punched.
40 mm deep.
1 x STS tray.
unpunched.
40 mm deep.

Optional accessories

BA046117
BA220360
BA220370
GN114130
GN114230
GN124130
GN124230

Product Variants

BSP221101

Flush installation
Water tank
Large cavity
LED light source
External steam generation
Steaming without pressure with 100% humidity from 30 °C to 100 °C
Sous-vide cooking with accurate temperature regulation
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 100 °C
59 litres net volume

Heating methods

100 % humidity.
Sous-vide cooking. Dough proofing.
Defrosting. Regenerating. Low temperature steaming.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Personalisation of automatic programmes.
Information key with use indications.
Side-opening door opens up to 110° angle.

Features

Removable 1.7 litre water tank.
Water level warning.
Actual temperature display.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).
Automatic boiling point detection.
LED light on the side.
Hygienic stainless steel cooking interior.
3 tray levels.

Selected digital services (Gaggenau Home Connect)

Remote control and monitoring.
Recipes.
Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Cleaning aid.
Descaling programme for the steam generator.

Planning notes

Door hinge not reversible.
No other electrical appliances should be installed above the BS.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Characteristics

Built-in / Free-standing

Built-in

Door opening

Lateral

Required niche size for installation (HxWxD)

450-450 x 560-560 x 550

Dimensions

455x590x540

Dimensions of the packed product (HxWxD)

590 x 660 x 700

Control Panel Material without panel

Door Material

Glass

Net weight

36.0

Length electrical supply cord

175.0

EAN code

4242006278205

Connection Rating

2750

Fuse protection

16

Voltage

220-240

Frequency

50-60

Plug type

Gardy plug w/ earthing

Included accessories

1 x grid, 1 x STS tray, punched, 40 mm deep, 1 x STS tray, unpunched, 40 mm deep

Consumption and connection features

created on 2025-08-23
Page 1

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the side-opening door and the minimum required distance to the wall.
The main socket needs to be planned outside of the niche.
The LAN port can be found at the back on the lower left side.
Special accessories (order as spare part):
Part No. 17002490 Descaling tablets.

Connection

Total connected load 2.8 KW.
Connecting cable 1.8 m with plug.
Plan a LAN cable.
Power consumption standby/display on 0.8 W.
Power consumption standby/display off 0.5 W.
Power consumption standby/network 1.8 W.
Time auto-standby/display on 20 min.
Time auto-standby/display off 20 min.#
Time auto-standby/network 20 min.
Please check the user manual for how to switch off the WiFi module.

