



BSP221110
Steam oven 200 Series
Full glass door in Gaggenau Metallic
Width 60 cm
Controls at the top

Flush installation
Water tank
Steaming without pressure with 100% humidity from 30 °C to 100 °C
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 30 °C to 100 °C

Heating methods
100 % humidity.
Slow steaming.
Dough proofing.
Defrosting.
Regenerating.
Low temperature steaming.

Handling
Rotary knob and TFT touch display operation.
Information key with use indications.
Side-opening door opens up to 110° angle.

Features
Removable 1.3 litre water tank.
Water level warning.
Actual temperature display.
Electronic boiling point detection.
60 W halogen light on the side.
Hygienic stainless steel cooking interior.
3 tray levels.

Safety
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning
Cleaning aid.
Descaling programme.

Planning notes
Door hinge not reversible.
No other electrical appliances should be installed above the BS.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Connection
Total connected load 1.9 KW.
Connection cable 1.5 m without plug.

Characteristics
Color / Material Front
Construction type
Built-in
Door opening
Lateral
Required niche size for installation (HxWxD)
Dimensions
455 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
575 x 660 x 690
Control Panel Material
Door Material
Glass
Net weight (kg)
34.308
Approval certificates
CE, VDE
Length of electrical supply cord (cm)
150
EAN code
4242006217433
Connection rating (W)
1900
Current (A)
8
Voltage (V)
220-240
Frequency (Hz)
50; 60
Plug type
fixed connection, no plug
Approval certificates
CE, VDE

Consumption and connection features
created on 2021-04-07
Page 1


Color Variants
BSP221110
Full glass door in Gaggenau Metallic
Width 60 cm
BSP221100
Full glass door in Gaggenau Anthracite
Width 60 cm

Included accessories
1 x STS tray-GN2/3-punched-40 mm deep.
1 x STS tray-GN2/3-unpunched-40 mm deep.
1 x grid.

Optional accessories
GN114130
Gastronorm insert, stainless steel, GN 1/3
GN114230
Gastronorm insert, stainless steel, GN 2/3
GN124130
Gastronorm insert, stainless steel, GN 1/3
GN124230
Gastronorm insert, stainless steel, GN 2/3
GN340230
Gastronorm roaster in cast aluminium

Product Variants
BSP220110
Steam oven 200 Series
Full glass door in Gaggenau Metallic
Width 60 cm
Controls at the top

BSP221110
Steam oven 200 Series
Full glass door in Gaggenau Metallic
Width 60 cm
Controls at the top
created on 2021-04-07
Page 2



Side view of BSP, BMP over BOP

