



**BSP250110**  
**Combi-steam oven 200 series**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**Controls at the top**

**A+**

Flush installation  
Water tank  
Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%  
TFT touch display  
Panel-free appliance with surface control module  
Steaming without pressure  
Electronic temperature control from 30 °C to 230 °C  
Core temperature probe, removable

#### Heating methods

Hot air + 100 % humidity.  
Hot air + 80 % humidity.  
Hot air + 60 % humidity.  
Hot air + 30 % humidity.  
Hot air + 0 % humidity.  
Dough proofing.  
Defrosting.  
Regenerating.  
Low temperature cooking.

#### Handling

Rotary knob and TFT touch display operation.  
Option to save individual recipes (incl. core temperature probe).  
Information key with use indications.  
Side-opening door opens up to 110° angle.

#### Features

Removable 1.3 litre water tank.  
Water level warning.  
Core temperature probe with automatic shut-off.  
Actual temperature display.  
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
Electronic boiling point detection.  
60 W halogen light on the side.  
Hygienic stainless steel cooking interior.  
3 tray levels.

#### Safety

Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

#### Cleaning

Cleaning aid.  
Drying programme.  
Descaling programme.  
Grease filter, dishwasher-safe.

#### Planning notes

Door hinge not reversible.  
No other electrical appliances should be installed above the BS.  
The door panel surface of the appliance extends 21 mm from the furniture cavity.  
The outer edge of the door handle extends 72 mm from the furniture cavity.  
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.  
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
When planning a corner solution, pay attention to the 110° door opening angle.  
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.  
The mains socket needs to be planned outside of the built-in niche.

#### Characteristics

**Color / Material Front**  
**Construction type**  
Built-in  
**Door opening**  
Lateral  
**Required niche size for installation (HxWxD)**  
**Dimensions**  
455 x 590 x 547  
**Dimensions of the packed product (HxWxD) (mm)**  
575 x 660 x 690  
**Control Panel Material**  
**Door Material**  
Glass  
**Net weight (kg)**  
35.908  
**Approval certificates**  
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE  
**Length of electrical supply cord (cm)**  
150  
**EAN code**  
4242006217341  
**Electrical connection rating (W)**  
**Current (A)**  
8  
**Voltage (V)**  
220-240  
**Frequency (Hz)**  
50; 60  
**Plug type**  
fixed connection, no plug  
**Approval certificates**  
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE  
**Number of cavities (2010/30/EC)**  
1  
**Usable volume (of cavity) - NEW (2010/30/EC)**  
42  
**Energy efficiency rating**  
A+  
**Energy consumption per cycle conventional (2010/30/EC)**  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
0.57  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
**Energy efficiency index (2010/30/EC)**  
78.1

#### Consumption and connection features

created on 2021-05-26  
Page 1

#### Color Variants

**BSP250110**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**BSP250100**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

#### Included accessories

1 x STS tray-GN2/3-punched-40 mm deep.  
1 x STS tray-GN2/3-unpunched-40 mm deep.  
1 x grid.  
1 x pluggable meat probe.

#### Optional accessories

**GN114130**  
Gastronorm insert, stainless steel, GN 1/3  
**GN114230**  
Gastronorm insert, stainless steel, GN 2/3  
**GN124130**  
Gastronorm insert, stainless steel, GN 1/3  
**GN124230**  
Gastronorm insert, stainless steel, GN 2/3  
**GN340230**  
Gastronorm roaster in cast aluminium

#### Product Variants

**BSP251110**  
**Combi-steam oven 200 series**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**Controls at the top**

## Connection

Total connected load 1.9 KW.  
Connection cable 1.5 m without plug.

# GAGGENAU

