

BSP251130 Combi-steam oven 200 series

Full glass door in Gaggenau Silver

Width 60 cm

Controls at the top

Water tank

Flush installation

Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%

TFT touch display

Panel-free appliance with surface control module

Steaming without pressure

Electronic temperature control from 30 °C to 230 °C

Core temperature probe, removable

Hot air + 100 % humidity.

Hot air + 80 % humidity.

Hot air + 60 % humidity.

Hot air + 30 % humidity.

Defrosting.

Regenerating.

Low temperature cooking.

1 x STS tray-GN2/3-punched-40 mm deep

Full glass door in Gaggenau Silver

Full glass door in Gaggenau Anthracite

Full glass door in Gaggenau Metallic

1 x STS tray-GN2/3-unpunched-40 mm deep.

1 x grid.

Color Variants

BSP251130

Width 60 cm

BSP251100

Width 60 cm

BSP251110

Width 60 cm

1 x pluggable meat probe.

Optional accessories

Included accessories

GN114130

Gastronorm insert, stainless steel, GN 1/3

GN114230

Gastronorm insert, stainless steel, GN 2/3

GN124130

Gastronorm insert, stainless steel, GN 1/3

GN124230

Gastronorm insert, stainless steel, GN 2/3

GN340230

Gastronorm roaster in cast aluminium

Product Variants

BSP250130

Combi-steam oven 200 series Full glass door in Gaggenau Silver Width 60 cm

Controls at the top

Heating methods

Hot air + 0 % humidity.

Dough proofing.

Handling

Rotary knob and TFT touch display operation.

Option to save individual recipes (incl. core temperature probe). Information key with use indications.

Side-opening door opens up to 110° angle.

Features

Removable 1.3 litre water tank. Water level warning.

Core temperature probe with automatic shut-off.

Actual temperature display.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term

Electronic boiling point detection. 60 W halogen light on the side. Hygienic stainless steel cooking

3 tray levels.

Safety

Child lock Safety shut-off.

Cooled housing with temperature

Cleaning Cleaning aid.

Drying programme.

Descaling programme.

Grease filter, dishwasher-safe.

Planning notes

Door hinge not reversible. No other electrical appliances should be installed above the BS.

The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture

cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front

Construction type

Built-in

Door opening Lateral

Required niche size for installation (HxWxD)

Connection

Total connected load 1.9 KW.

Connection cable 1.5 m without plug.

Dimensions

455 x 590 x 547

Dimensions of the packed product

(HxWxD) (mm) 575 x 660 x 690

Control Panel Material

Door Material

Net weight (kg)

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (cm)

EAN code

4242006217396

Electrical connection rating (W)

Current (A)

Voltage (V)

220-240 Frequency (Hz)

50: 60

Plug type

fixed connection, no plug

Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE

Number of cavities (2010/30/EC)

Usable volume (of cavity) - NEW

(2010/30/EC)

Energy efficiency rating

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle

conventional (2010/30/EC) Energy consumption per cycle forced air convection (2010/30/EC)

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Consumption and connection features

created on 2021-02-22 Page 1



BSP251130
Combi-steam oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
Controls at the top

created on 2021-02-22 Page 2





